U/V Tuner Board with Hospitality Port

TY-FB8TA

■ Product summary

- Designed to fit in the interchangeable slots of Series-9 plasma models to provide easy and sleek in-hotel TV solution (compatible plasma models and slots as designated in the specification below).
- AV In&Out ports are available for the connection with in-room local AV equipments (like VCR, DVD).
- Switch-able between Normal TV mode and Hotel mode (Hotel mode allows you to set initial channel, max volume, etc.).
- IR through-out port allows you to co-use IR sensor on plasma display to control both TV and STB
- Available with optional Set Up Loader – enables you to easily make same setting on multiple TVs.

■ Products specification (Design and specifications subject to change without notice)

Slot Compatibility		
	PWD8 Series	Slot 1 & Slot 2
	PG9 Series	Slot 2 & Slot 3
	PS9, PH9 Series	Slot 2 & Slot 3

Receiving System				
	17 Systems			
	1	PAL B, G, H	10	NTSC 4.43/6.5 MHz
	2	PAL I	11	NTSC 3.58/5.5 MHz
	3	PAL D, K	12	NTSC 3.58/6.0 MHz
	4	SECAM B, G	13	NTSC 3.58/6.5 MHz
	5	SECAM D, K	14	SECAM I
	6	SECAM K1	15	PAL 60 Hz/5.5 MHz
	7	NTSC M (NTSC 3.58/4.5 MHz)	16	PAL 60 Hz/6.0 MHz
	8	NTSC 4.43/5.5 MHz	17	PAL 60 Hz/6.5 MHz
	9	NTSC 4.43/6.0 MHz		

Receiving Channels			
	VHF BAND	**UHF BAND**	**CATV**
	2-12 (PAL/SECAM B, K1)	21-69 (PAL G, H, I/SECAM G, K, K1)	S1-S20 (OSCAR)
	0-12 (PAL B AUST.)	28-69 (PAL B AUST.)	1-125 (U.S.A. CATV)
	1-9 (PAL B N.Z)	13-57 (PAL D, K)	C13-C49 (JAPAN)
	1-12 (PAL/SECAM D)	13-62 (NTSC M Japan)	S21-S41 (HYPER)
	1-12 (NTSC M Japan)	14-69 (NTSC M U.S.A.)	Z1-Z37 (CHINA)
	2-13 (NTSC M U.S.A.)		5A, 9A (AUST.)

INPUT / OUTPUT		
	RF IN x 1	
	VIDEO IN	BNC Composit x 1 — 1.0 Vp-p / 75 Ω
		S-VIDEO x 1 — Y : 1.0 Vp-p / 75 Ω
		C: 0.286 Vp-p / 75 Ω (NTSC)
		C: 0.3 Vp-p / 75 Ω (PAL)
	AUDIO IN (L/R)	RCA pin jack x 2 — 0.5 Vrms
	VIDEO OUT	BNC Composit x 1 — 1.0 Vp-p /75 Ω
	AUDIO OUT (L/R)	RCA pin jack x 2 — 0.5 Vrms
	Hospitality port	RJ-45 x 1
	Remote Control through out	M3 jack x 1

Applicable models	PWD8 Series, PG9 Series, PS9/PH9 Series
Weight	550 g (1.21 lbs)
Included Accessories	Terminal function label x 1 Screw x 4 Ir system cord x 1
	Remote control Batteies

■ Dimensions

148.9 (5.86)

209.5 (8.25)

38.5 (1.52)

AUDIO IN (L-R)
S-VIDEO IN
VIDEO IN
VIDEO OUT

Remote Control through out terminal
VHF/UHF
Hospitality port
AUDIO OUT (L-R)