

List of Compatible Device Models

Logo Transfer Software

- As of November 2020 -

In using this software, bear in mind that the items whose settings must be selected for the projectors and the functions that can be used may differ from one projector model to another. While referring to the table below, check out that projector models are compatible with the software before using them.

List of models

PT-D10000	13	PT-DX610	11
PT-D12000	10	PT-DX800	11
PT-D4000	14	PT-DX810	11
PT-D5000	11	PT-DX820	7
PT-D5700	14	PT-DZ10K	7
PT-D6000	11	PT-DZ110XE	11
PT-DS100XE	11	PT-DZ12000	10
PT-DS12K	7	PT-DZ13K	7
PT-DS20K	7	PT-DZ16K	7
PT-DS20K2	7	PT-DZ16K2	7
PT-DS8500	11	PT-DZ21K	7
PT-DW100	10	PT-DZ21K2	7
PT-DW10000	13	PT-DZ570	12
PT-DW105XEA	11	PT-DZ6700	11
PT-DW11K	7	PT-DZ6710	11
PT-DW17K	7	PT-DZ680	11
PT-DW17K2	7	PT-DZ770	11
PT-DW5100	14	PT-DZ780	7
PT-DW530	12	PT-DZ870	7
PT-DW6300	11	PT-DZ8700	11
PT-DW640	11	PT-EW530	19
PT-DW730	11	PT-EW540	17
PT-DW740	11	PT-EW550	18
PT-DW750	7	PT-EW551	18
PT-DW830	7	PT-EW630	19
PT-DW8300	11	PT-EW640	17
PT-DW90XE	11	PT-EW650	18
PT-DX100	7	PT-EW651	18
PT-DX500	12	PT-EW730	17

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-EX12K	20	PT-MW630	7
PT-EX16K	20	PT-MW730	7
PT-EX500	19	PT-MZ10K	7
PT-EX510	17	PT-MZ13K	7
PT-EX520	18	PT-MZ16K	7
PT-EX521	18	PT-MZ570	7
PT-EX600	19	PT-MZ670	7
PT-EX610	17	PT-MZ770	7
PT-EX620	18	PT-RCQ10	6
PT-EX621	18	PT-RCQ80	6
PT-EX800	17	PT-RQ13K	7
PT-EZ57	18	PT-RQ22K	7
PT-EZ570	19	PT-RQ32K	7
PT-EZ580	17	PT-RQ35K	5
PT-EZ590	18	PT-RQ50K	4
PT-EZ591	18	PT-RS11K	7
PT-EZ770	17	PT-RS20K	7
PT-FRZ50	7	PT-RS30K	7
PT-FRZ55	7	PT-RW330	9
PT-FRZ60	7	PT-RW430	9
PT-FW430	26	PT-RW620	7
PT-FW530	18	PT-RW630	7
PT-FX400	26	PT-RW730	7
PT-FX500	18	PT-RW930	7
PT-FZ570	18	PT-RX110	7
PT-LB1	30	PT-RZ120	7
PT-LB1V	30	PT-RZ12K	7
PT-LB2	30	PT-RZ16K	7
PT-LB2V	30	PT-RZ21K	7
PT-LB3	30	PT-RZ31K	7
PT-LB306	16	PT-RZ34K	5
PT-LB356	15	PT-RZ370	9
PT-LB386	15	PT-RZ470	9
PT-LB426	15	PT-RZ475	9
PT-LB75V	31	PT-RZ570	7
PT-LB78V	31	PT-RZ575	7
PT-LB90	31	PT-RZ660	7
PT-LB90NT	30	PT-RZ670	7
PT-LW25H	29	PT-RZ690	7
PT-LW336	15	PT-RZ770	7
PT-LW376	15	PT-RZ790	7
PT-LX22	29	PT-RZ870	7
PT-LX26	29	PT-RZ890	7
PT-LX26H	29	PT-RZ970	7
PT-LX30H	29	PT-RZ990	7
PT-LZ370	28	PT-ST10	30
PT-MW530	7	PT-SW280A	27

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-SX300A	27	PT-VX60	22
PT-SX320A	27	PT-VX600	22
PT-TW230	29	PT-VX605N	22
PT-TW231R	29	PT-VX61	21
PT-TW380	15	PT-VX610	21
PT-TW381R	15	PT-VX615N	21
PT-TX350	15	PT-VZ470	22
PT-TX440	15	PT-VZ570	22
PT-VMW50	18	PT-VZ575N	22
PT-VMW60	18	PT-VZ580	21
PT-VMZ40	18	PT-VZ585N	21
PT-VMZ50	18	TH-D10000	13
PT-VMZ60	18	TH-DW10000	13
PT-VW330	25		
PT-VW340	22		
PT-VW345N	22		
PT-VW350	22		
PT-VW355N	22		
PT-VW360	22		
PT-VW430	23		
PT-VW431D	24		
PT-VW435N	23		
PT-VW440	23		
PT-VW530	22		
PT-VW535N	22		
PT-VW540	21		
PT-VW545N	21		
PT-VX400	25		
PT-VX400NT	25		
PT-VX405	23		
PT-VX406	22		
PT-VX41	25		
PT-VX410	22		
PT-VX415N	22		
PT-VX42	22		
PT-VX420	22		
PT-VX421	22		
PT-VX425N	22		
PT-VX430	22		
PT-VX45	23		
PT-VX46	22		
PT-VX50	22		
PT-VX500	23		
PT-VX501	23		
PT-VX505N	23		
PT-VX51	21		
PT-VX510	23		

The software is not compatible with any device models that are not listed in "List of models".

PT-RQ50K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/X/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 2048 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RQ35K / PT-RZ34K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RCQ10 / PT-RCQ80

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/J/X/(blank), lens: L/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	×	
	Communication rate (bps)	×	
	Parity	×	
	Projector ID	×	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	—	
	On and during display of password input screen immediately after power on	—	
	On and following password input immediately after power on	—	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-RQ32K / PT-RZ31K / PT-RS30K
 ■ PT-RQ13K
 ■ PT-RQ22K / PT-RZ21K / PT-RS20K
 ■ PT-RZ12K / PT-RS11K
 ■ PT-RZ16K
 ■ PT-RZ990 / PT-RZ890 / PT-RZ790 / PT-RZ690
 ■ PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
 ■ PT-RZ670 / PT-RW630
 ■ PT-FRZ60 / PT-FRZ50 / PT-FRZ55
 ■ PT-RZ575 / PT-RZ570
 ■ PT-DZ21K2 / PT-DS20K2 / PT-DW17K2 / PT-DZ16K2
 ■ PT-DZ21K / PT-DS20K / PT-DW17K / PT-DZ16K
 ■ PT-DZ13K / PT-DS12K / PT-DW11K / PT-DZ10K
 ■ PT-DZ870 / PT-DW830 / PT-DX100
 ■ PT-DZ780 / PT-DW750 / PT-DX820
 ■ PT-MZ16K / PT-MZ13K / PT-MZ10K
 ■ PT-MZ770 / PT-MW730 / PT-MZ670 / PT-MW630 / PT-MZ570 / PT-MW530

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/E/J/T/U/X/(blank), lens: L/(blank), cabinet color: B/K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

 PT-RZ475
 PT-RZ470 / PT-RW430
 PT-RZ370 / PT-RW330

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank), cabinet color: K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	×	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-DZ12000 / PT-D12000 / PT-DW100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	Transfer operations using a LAN connection cannot be performed if network standby is OFF.
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ8700 / PT-DS8500 / PT-DW8300 / PT-DZ110XE / PT-DS100XE / PT-DW90XE / PT-DW105XEA
 ■ PT-DZ770 / PT-DW740 / PT-DX810
 ■ PT-DZ680 / PT-DW640 / PT-DX610
 ■ PT-DZ6710 / PT-DZ6700 / PT-DW6300 / PT-D6000 / PT-D5000
 ■ PT-DW730 / PT-DX800

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank), cabinet color: S/K/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ570 / PT-DW530 / PT-DX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	ALL, 1 to 6 are generally available.
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ TH-DW10000 / TH-D10000 / PT-DW10000 / PT-D10000

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-D5700 / PT-D4000 / PT-DW5100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-LB426 / PT-LB386 / PT-LB356 / PT-LW376 / PT-LW336

■ PT-TW381R / PT-TW380 / PT-TX440 / PT-TX350

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

*1: Background color can be set only for the PT-LW376, PT-LW336, PT-TW381R and PT-TW380.

PT-LB306

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: (blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	X	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

■ PT-EZ770 / PT-EW730 / PT-EX800

■ PT-EZ580 / PT-EW640 / PT-EX610 / PT-EW540 / PT-EX510

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/Z/T/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-EZ590 / PT-EW650 / PT-EW550 / PT-EX620 / PT-EX520 / PT-EZ57
PT-EZ591 / PT-EW651 / PT-EW551 / PT-EX621 / PT-EX521
PT-FZ570 / PT-FW530 / PT-FX500
PT-VMZ60 / PT-VMZ50 / PT-VMZ40 / PT-VMW60 / PT-VMW50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/J/K/T/(blank), lens: L/(blank), cabinet color: B/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ590, PT-EW650, PT-EW550, PT-EZ57, PT-EZ591, PT-EW651, PT-EW551, PT-FZ570, PT-FW530, PT-VMZ60, PT-VMZ50, PT-VMZ40, PT-VMW60 and PT-VMW50.

■ PT-EZ570 / PT-EW630 / PT-EX600 / PT-EW530 / PT-EX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal, Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ570, PT-EW630 and PT-EW530.

PT-EX16K
PT-EX12K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-VZ585N / PT-VW545N / PT-VX615N

■ PT-VZ580 / PT-VW540 / PT-VX610 / PT-VX61 / PT-VX51

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/K/K1/T/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-VZ575N / PT-VW535N / PT-VX605N
PT-VZ570 / PT-VW530 / PT-VX600 / PT-VX406 / PT-VX46 / PT-VX60 / PT-VX50
PT-VZ470
PT-VW360 / PT-VX430
PT-VW355N / PT-VX425N
PT-VW350 / PT-VX420 / PT-VX421
PT-VW345N / PT-VX415N
PT-VW340 / PT-VX410 / PT-VX42

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/EA/J/T/Z/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VZ575N, PT-VW535N, PT-VZ570, PT-VW530, PT-VZ470, PT-VW360, PT-VW355N, PT-VW350, PT-VW345N and PT-VW340.

■ PT-VW440 / PT-VX510

■ PT-VW435N / PT-VX505N / PT-VW430 / PT-VX501 / PT-VX500 / PT-VX405 / PT-VX45

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/EP/KEA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW440, PT-VW435N and PT-VW430.

PT-VW431D

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-VW330 / PT-VX400NT / PT-VX400 ■ PT-VX41

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW330.

PT-FW430 / PT-FX400

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-SW280A / PT-SX320A / PT-SX300A

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-SW280A.

PT-LZ370

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LW25H / PT-LX30H / PT-LX26H / PT-LX26 / PT-LX22 **PT-TW231R / PT-TW230**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-LW25H, PT-TW231R and PT-TW230.

PT-LB90NT

PT-LB3 / PT-LB2V / PT-LB2 / PT-LB1V / PT-LB1 / PT-ST10

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible X: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	X	
	Standby	○ (Standby mode: Normal)	
	During cooling	X	
	During power on process	X	
Security password setting	On and standby state	X	
	On and during display of password input screen immediately after power on	X	
	On and following password input immediately after power on	X	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible X: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	X	
	Background color specification	X	
Enlarge	Display enlargement function on projector side	X	
Display position	Display at any position	X	

PT-LB90 / PT-LB78V / PT-LB75V

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	