

## WV-SFV781L/SPV781L Firmware Release Note

VER (ActiveX Ver) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
Ver1.05 (4.37.03) June, '15	-					First production		
Ver1.06 (4.37.04) Aug., '15	C			x		White line may be seen.	When the black-and-white image state.	Fixed.
				x		Unable to adjust zooming ratio 4.3x by slide-bar of Zoom ratio designation at Zoom/focus adjustment	-	Fixed.
					x	-	-	Improved by reducing the 8-Megapixel[16:9](30fps mode) of H.264(1) time of transmission until the start.
				x		In CGI command, capability information responded incorrect parameter about "drag_zoom" and "default_zoom". (Occurrence frequency : High)	-	Fixed.
					x	-	-	Added information of capability by CGI command; - available modes supporting VIQS. - available range for VMD area.
					x	-	-	Improved on CGI command, it would accept and respond to keep_alive, while cropping [16:9] (30fps) mode, even comes with unnecessary ch information. (It was responded an error).
					x	Chang of time zone setting may not be effected even if it would be synchronized.	When changing time zone setting after changing Time adjustment by NTP from "Off" to "On".	Fixed.
					x	May not display camera image in 4-screen or 9-screen on WJ-NV300.	Under the conditions as follow; - Registering WV-SFV481/WV-SFN480. - Set camera to be multicast. - Changed the setting of "Upside-down" from "On (desktop)" to "Wall" by WJ-NV300.	Fixed.
Ver1.07 (4.37.04) Sept., '15	C			x	Camera would be rarely restarted while streaming due to an encode error. (Occurrence frequency : Low)	When the load of the camera is high.	Fixed.	
				x	Transmitting 1.5fps even if the frame rate of H.264 were set 1fps.	In a case, setting one of the following; - 8-Megapixel [16:9] (15fps mode) : H.264(2) - 12-Megapixel [4:3] (15fps mode) : H.264(1) - 5-Megapixel [4:3] (30fps mode) : H.264(1), H.264(2) - 4-Megapixel [16:9] (30fps mode) : H.264(1) to H.264(4) - Cropping [16:9] (30fps mode) : H.264(1), H.264(2)	Fixed.	

## WV-SFV781L/SPV781L Firmware Release Note

VER (ActiveX Ver) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
Ver2.01 (4.38.08) Feb., '16	C				x	-	-	Made encrypting the firmware. To upgrade the firmware from version 1.15 or older, required 2-step upgrading; - First step: upgrade to version 9.99. - Second step: upgrade to version 2.01.
					x	-	-	Added "Smart Coding mode" function.
					x	-	-	Supported Safari/Firefox/Google Chrome at configuration settings Note: Tested version; - Safari: Version 5.34.57 - Google Chrome: Version 44.0.2403 (Except displaying H.264 images) - Firefox: Version 39.0.0
					x	-	-	Support upgrading firmware by CGI command (StartFirmwareUpgrade).
				x		Wrote settings onto the Flash-ROM by clicking the "Set" button on menu setting page even if nothing changed. (Occurrence frequency : High)	-	Fixed.
					x	-	-	Changed the word in Chinese at SD memory card information (SD记忆卡信息) in System log (系统日志); [Prev.] 错误内容 (Description) [New] 内容 (Description)
					x	-	-	Changed response to the CGI commands; "/cgi-bin/get_capability" : Added about SD card recorder. "/cgi-bin/get_capability2" : Added capture size for 4K cameras.
					x	-	-	Corrected the vulnerability by upgrading OSS for NTP; [Prev.] ntp-4.2.6 p3 [New] ntp-4.2.8 p4
			x	Maintenance page layout may collapse. (Occurrence frequency : High)	In the page of User mng.	Fixed.		
Ver2.02 (4.38.08) Mar., '16	U				x	-	-	Added a notice for each screen that alarm notification will not be appeared while displaying VMD and audio detection.
Ver2.04 (4.38.08) Mar., '16	C			x	No images were output after upgrading firmware from version 1.xx to 2.xx.	While the image capture mode is set either "4 mega pixel [16:9](30fps mode)" or "Cropping [16:9](30fps)".	Fixed.	
Ver2.40 (4.38.08) Apr., '16	C				x	Except Chinese market models (WV-SFV781LH/WV-SPV781LH).		Added a choice to select a certification when using HTTPS. This is effective from products manufactured in April, 2016. Those serial numbers are as follow; "PDxxxxxx", PExxxxxx, PFxxxxxx and after. "Qxxxxxxx", Rxxxxxxx and after.
						-	-	

## WV-SFV781L/SPV781L Firmware Release Note

VER (ActiveX Ver) Release Date	Priority Rank Level	Priority Rank Level				Contents			
		A	B	C	U	Issue (Phenomenon)	Occurrence condition	Correspondence	
Ver2.40 (4.38.08) Apr.,'16	C				x	-	-	1. Changed factory default setting value at User Authentication from "OFF" to "ON". 2. Deleted pre-registered User name (admin), and Password (12345). 3. All users must register User name(s) and Password(s) at initial access. - User name: 1 to 32 characters - Password; 8 to 32 characters, two or more types of characters among alphabets, numbers and symbols. Note: Currently registered User name(s) and Password(s) will NOT be deleted by upgrading firmware, however, you have to register them under the new policy (above "3") after initializing (default reset) by the INITIAL SET button or by the setup menu.	
Ver2.43 (4.38.08) June,'16	C			x		Unable to connect the cameras by the HTTPS protocol.	After turning power off and on if the connection protocol were configured in "HTTPS" and using with the Root Certification Authorities (CA).	Fixed.	
Ver2.50 (4.39.00) July,'16	C				x	-	-	Corrected the vulnerability by upgrading OSS for NTP; [Prev.] ntp-4.2.6 p4 [New] ntp-4.2.8 p7	
					x	-	-	Added choices of "Bandwidth control(bit rate)". 1024kbps/15360kbps/20480kbps/25600kbps/30720kbps/35840kbps/40960kbps/51200kbps	
					x	-	-	Added choices of "On(Mid)" and "On(High)" to "Smart Coding mode".	
					x	-	-	OnVIF: Supported "WS Addressing".	
					x	-	-	Added information about place of product destination and model number with suffix to the reply of CGI command "/cgi-bin/getinfo".	
					x	-	-	Updated hyperlink to the web sites of support.	
				x			Layout of image display may be collapsed.	By inputting "</script>" at input-field.	Fixed.
				x			Stereo audio may be played back in monaural.	-	Fixed.
					x		Unable to transmit MotionJPEG with configured picture size at JPEG(2) by CGI command, "/cgi-bin/nphMotionJpeg".	While image capture mode were in "4M Fisheye".	Fixed.
			x		Unable to change settings of "Transmission priority" and "Refresh interval" simultaneously by CGI command, "/cgi-bin/set_h264".	On firmware version between 2.01 and 2.43.	Fixed.		
				x	Setting of "Refresh interval" left "8s" internally (should become "1s") even if settings both "Smart coding = On" and "H.264 streaming = SD" although "Smart coding" become "Off". As a result, recording in H.264 on SD memory card may be abnormal.	-	Fixed.		
				x	The camera may restart, unexpectedly.	In a case, connect/disconnect H.264 streaming , repeatedly.	Fixed.		

## WV-SFV781L/SPV781L Firmware Release Note

VER (ActiveX Ver) Release Date	Priority Rank Level	Priority Rank Level				Contents		
		A	B	C	U	Issue (Phenomenon)	Occurrence condition	Correspondence
Ver2.52 (4.39.00) Dec., '16	C			x		The Real-time Pull-Point Notification Interface did not conform to ONVIF.	-	Fixed.
					x	-	-	Improved security.
Ver2.53 (4.39.00) Feb., '17	C			x		Did not work data encryption during over RTSP streaming.	-	Fixed.
				x		RTSP distribution may be stopped during continuous operation.	Streaming to WJ-NX400 (Network Disk Recorder).	Fixed.
				x		Changing frame rate dynamically by CGI command at the time of an alarm may not be effected on camera.	While operating with WJ-NX400 (Network Disk Recorder).	Fixed.
Ver2.54 (4.39.00) May, '17	C			x		Unable to work time adjustment function synchronizing with NTP server.	When the difference between the clock and the NTP server is within 5 seconds.	Fixed.
					x	Refresh interval may be switched to "8s", unexpectedly.	By changing "Transmission priority" of H.264 for the options other than "VBR", initiated by PSSCT or WJ-NV300 only if it is the first time from the installation of the camera.	Fixed.
Added on May 31, 2017								
Ver2.56 (4.39.23) Sept., '17	C				x	-	-	Changed company name to the new company name in the plug-in (ActiveX) software.
					x	-	-	Updated the URL of support website displayed on screen.
Ver2.58 (4.39.23) Mar., '18					x	-	-	Improved security.
					x	-	-	In CGI command of "get_io2", added new parameter "3" for "format" so that possible to obtain Command alarm / i-VMD information.
					x	-	-	Added new Panasonic alarm notifications as follow; SD-MEMORY WRITE ERROR SD-MEMORY READ ERROR SD-MEMORY DELETE ERROR SD-MEMORY FILESYSTEM ERROR SD-MEMORY OTHER ERROR
					x	-	-	Discarded a restriction that only "Unicast port (AUTO)" in RTSP transmission would be available when "Transmission type" is "On".
				x		Leaked POST connection.	in a case of disconnect network in "over HTTP" for 2 and half minutes or more.	Fixed.
				x		Image capture size may become incorrect.	By setting Image capture size from Image Viewer.	Fixed.
			x	Administrator password may be deleted.	-	Fixed.		