

List of Compatible Device Models

Logo Transfer Software

- As of October 2019 -

In using this software, bear in mind that the items whose settings must be selected for the projectors and the functions that can be used may differ from one projector model to another. While referring to the table below, check out that projector models are compatible with the software before using them.

List of models

PT-D10000	12	PT-DX610	10
PT-D12000	9	PT-DX800	10
PT-D4000	13	PT-DX810	10
PT-D5000	10	PT-DX820	6
PT-D5700	13	PT-DZ10K	6
PT-D6000	10	PT-DZ110XE	10
PT-DS100XE	10	PT-DZ12000	9
PT-DS12K	6	PT-DZ13K	6
PT-DS20K	6	PT-DZ16K	6
PT-DS20K2	6	PT-DZ16K2	6
PT-DS8500	10	PT-DZ21K	6
PT-DW100	9	PT-DZ21K2	6
PT-DW10000	12	PT-DZ570	11
PT-DW105XEA	10	PT-DZ6700	10
PT-DW11K	6	PT-DZ6710	10
PT-DW17K	6	PT-DZ680	10
PT-DW17K2	6	PT-DZ770	10
PT-DW5100	13	PT-DZ780	6
PT-DW530	11	PT-DZ870	6
PT-DW6300	10	PT-DZ8700	10
PT-DW640	10	PT-EW530	16
PT-DW730	10	PT-EW540	14
PT-DW740	10	PT-EW550	15
PT-DW750	6	PT-EW551	15
PT-DW830	6	PT-EW630	16
PT-DW8300	10	PT-EW640	14
PT-DW90XE	10	PT-EW650	15
PT-DX100	6	PT-EW651	15
PT-DX500	11	PT-EW730	14

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-EX12K	17	PT-RCQ80	5
PT-EX16K	17	PT-RQ13K	6
PT-EX500	16	PT-RQ22K	6
PT-EX510	14	PT-RQ32K	6
PT-EX520	15	PT-RQ50K	4
PT-EX521	15	PT-RS11K	6
PT-EX600	16	PT-RS20K	6
PT-EX610	14	PT-RS30K	6
PT-EX620	15	PT-RW330	8
PT-EX621	15	PT-RW430	8
PT-EX800	14	PT-RW620	6
PT-EZ57	15	PT-RW630	6
PT-EZ570	16	PT-RW730	6
PT-EZ580	14	PT-RW930	6
PT-EZ590	15	PT-RX110	6
PT-EZ591	15	PT-RZ120	6
PT-EZ770	14	PT-RZ12K	6
PT-FW430	23	PT-RZ21K	6
PT-FW530	15	PT-RZ31K	6
PT-FX400	23	PT-RZ370	8
PT-FX500	15	PT-RZ470	8
PT-FZ570	15	PT-RZ475	8
PT-LB1	27	PT-RZ570	6
PT-LB1V	27	PT-RZ575	6
PT-LB2	27	PT-RZ660	6
PT-LB2V	27	PT-RZ670	6
PT-LB3	27	PT-RZ770	6
PT-LB75V	28	PT-RZ870	6
PT-LB78V	28	PT-RZ970	6
PT-LB90	28	PT-ST10	27
PT-LB90NT	27	PT-SW280A	24
PT-LW25H	26	PT-SX300A	24
PT-LX22	26	PT-SX320A	24
PT-LX26	26	PT-TW230	26
PT-LX26H	26	PT-TW231R	26
PT-LX30H	26	PT-VMW50	15
PT-LZ370	25	PT-VMW60	15
PT-MW530	6	PT-VMZ40	15
PT-MW630	6	PT-VMZ50	15
PT-MW730	6	PT-VMZ60	15
PT-MZ10K	6	PT-VW330	22
PT-MZ13K	6	PT-VW340	19
PT-MZ16K	6	PT-VW345N	19
PT-MZ570	6	PT-VW350	19
PT-MZ670	6	PT-VW355N	19
PT-MZ770	6	PT-VW360	19
PT-RCQ10	5	PT-VW430	20

(continued)

The software is not compatible with any device models that are not listed in "List of models".

List of models

(continued)

PT-VW431D	21
PT-VW435N	20
PT-VW440	20
PT-VW530	19
PT-VW535N	19
PT-VW540	18
PT-VW545N	18
PT-VX400	22
PT-VX400NT	22
PT-VX405	20
PT-VX406	19
PT-VX41	22
PT-VX410	19
PT-VX415N	19
PT-VX42	19
PT-VX420	19
PT-VX421	19
PT-VX425N	19
PT-VX430	19
PT-VX45	20
PT-VX46	19
PT-VX50	19
PT-VX500	20
PT-VX501	20
PT-VX505N	20
PT-VX51	18
PT-VX510	20
PT-VX60	19
PT-VX600	19
PT-VX605N	19
PT-VX61	18
PT-VX610	18
PT-VX615N	18
PT-VZ470	19
PT-VZ570	19
PT-VZ575N	19
PT-VZ580	18
PT-VZ585N	18
TH-D10000	12
TH-DW10000	12

The software is not compatible with any device models that are not listed in "List of models".

PT-RQ50K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/X/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	×
	Communication rate (bps)	×
	Parity	×
	Projector ID	×
Power state	Power on	×
	Standby	○
	During cooling	×
	During power on process	×
Security password setting	On and standby state	—
	On and during display of password input screen immediately after power on	—
	On and following password input immediately after power on	—

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 2048 X 1080	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RCQ10 / PT-RCQ80

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/E/J/X/(blank), lens: L/(blank), cabinet color: B/W)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	×
	Communication rate (bps)	×
	Parity	×
	Projector ID	×
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	—
	On and during display of password input screen immediately after power on	—
	On and following password input immediately after power on	—

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1920 X 1200	
	Number of colors	Max. 16777216 colors (24-bit color)	When creating a new file (loading a bitmap), it is automatically converted to the correct number of colors.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	The following formats are not supported: Top-down, transparent data
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

- PT-RQ32K / PT-RZ31K / PT-RS30K
- PT-RQ13K
- PT-RQ22K / PT-RZ21K / PT-RS20K
- PT-RZ12K / PT-RS11K
- PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
- PT-RZ670 / PT-RW630
- PT-RZ575 / PT-RZ570
- PT-DZ21K2 / PT-DS20K2 / PT-DW17K2 / PT-DZ16K2
- PT-DZ21K / PT-DS20K / PT-DW17K / PT-DZ16K
- PT-DZ13K / PT-DS12K / PT-DW11K / PT-DZ10K
- PT-DZ870 / PT-DW830 / PT-DX100
- PT-DZ780 / PT-DW750 / PT-DX820
- PT-MZ16K / PT-MZ13K / PT-MZ10K
- PT-MZ770 / PT-MW730 / PT-MZ670 / PT-MW630 / PT-MZ570 / PT-MW530

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/E/J/T/U/X/(blank), lens: L/(blank), cabinet color: B/K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-RZ475
PT-RZ470 / PT-RW430
PT-RZ370 / PT-RW330

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank), cabinet color: K/W/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	×	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-DZ12000 / PT-D12000 / PT-DW100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	Transfer operations using a LAN connection cannot be performed if network standby is OFF.
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ8700 / PT-DS8500 / PT-DW8300 / PT-DZ110XE / PT-DS100XE / PT-DW90XE / PT-DW105XEA

■ PT-DZ770 / PT-DW740 / PT-DX810

■ PT-DZ680 / PT-DW640 / PT-DX610

■ PT-DZ6710 / PT-DZ6700 / PT-DW6300 / PT-D6000 / PT-D5000

■ PT-DW730 / PT-DX800

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank), cabinet color: S/K/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ570 / PT-DW530 / PT-DX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	ALL, 1 to 6 are generally available.
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ TH-DW10000 / TH-D10000 / PT-DW10000 / PT-D10000

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U)

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	○
	Standby	○
	During cooling	○
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	○

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-D5700 / PT-D4000 / PT-DW5100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-EZ770 / PT-EW730 / PT-EX800

■ PT-EZ580 / PT-EW640 / PT-EX610 / PT-EW540 / PT-EX510

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/Z/T/(blank), lens: L/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

PT-EZ590 / PT-EW650 / PT-EW550 / PT-EX620 / PT-EX520 / PT-EZ57
PT-EZ591 / PT-EW651 / PT-EW551 / PT-EX621 / PT-EX521
PT-FZ570 / PT-FW530 / PT-FX500
PT-VMZ60 / PT-VMZ50 / PT-VMZ40 / PT-VMW60 / PT-VMW50

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: A/D/J/K/T/(blank), lens: L/(blank), cabinet color: B/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ590, PT-EW650, PT-EW550, PT-EZ57, PT-EZ591, PT-EW651, PT-EW551, PT-FZ570, PT-FW530, PT-VMZ60, PT-VMZ50, PT-VMZ40, PT-VMW60 and PT-VMW50.

PT-EZ570 / PT-EW630 / PT-EX600 / PT-EW530 / PT-EX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal, Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-EZ570, PT-EW630 and PT-EW530.

PT-EX16K
PT-EX12K

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-VZ585N / PT-VW545N / PT-VX615N

■ PT-VZ580 / PT-VW540 / PT-VX610 / PT-VX61 / PT-VX51

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/J/K/K1/T/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

- PT-VZ575N / PT-VW535N / PT-VX605N
- PT-VZ570 / PT-VW530 / PT-VX600 / PT-VX406 / PT-VX46 / PT-VX60 / PT-VX50
- PT-VZ470
- PT-VW360 / PT-VX430
- PT-VW355N / PT-VX425N
- PT-VW350 / PT-VX420 / PT-VX421
- PT-VW345N / PT-VX415N
- PT-VW340 / PT-VX410 / PT-VX42

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: D/EA/J/T/Z/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VZ575N, PT-VW535N, PT-VZ570, PT-VW530, PT-VZ470, PT-VW360, PT-VW355N, PT-VW350, PT-VW345N and PT-VW340.

■ PT-VW440 / PT-VX510

■ PT-VW435N / PT-VX505N / PT-VW430 / PT-VX501 / PT-VX500 / PT-VX405 / PT-VX45

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/EP/KEA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Network)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW440, PT-VW435N and PT-VW430.

PT-VW431D

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Network)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-VW330 / PT-VX400NT / PT-VX400
PT-VX41

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-VW330.

PT-FW430 / PT-FX400

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-SW280A / PT-SX320A / PT-SX300A

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-SW280A.

PT-LZ370

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “X”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LW25H / PT-LX30H / PT-LX26H / PT-LX26 / PT-LX22
PT-TW231R / PT-TW230

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

*1: Background color can be set only for the PT-LW25H, PT-TW231R and PT-TW230.

PT-LB90NT

PT-LB3 / PT-LB2V / PT-LB2 / PT-LB1V / PT-LB1 / PT-ST10

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

PT-LB90 / PT-LB78V / PT-LB75V

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

* Alphabet letters at end (place of destination: E/EA/U/(blank))

[Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

*1: The setting values cannot be changed.

[Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	