

CERTIFICATE OF COMPLIANCE

Certificate Number 20180606-E140407
Report Reference E140407-A428-UL
Issue Date 2018-JUNE-06

Issued to: Panasonic Corporation of North America
Product Safety & Compliance Dept
Two Riverfront Plaza
9th Fl, Newark NJ 07102-5490

**This is to certify that
representative samples of**

INFORMATION TECHNOLOGY EQUIPMENT INCLUDING
ELECTRICAL BUSINESS EQUIPMENT

Product:-Network Camera
Model:-WV-X8570N, WV-S8530N

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07 Standard
for Information Technology Equipment - Safety - Part 1:
General Requirements

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



UL TEST REPORT AND PROCEDURE

Standard:	UL 60950-1, 2nd Edition, 2014-10-14 (Information Technology Equipment - Safety - Part 1: General Requirements) CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 (Information Technology Equipment - Safety - Part 1: General Requirements)
Certification Type:	Listing
CCN:	NWQQ, NWQQ7 (Information Technology Equipment Including Electrical Business Equipment)
Product:	Network Camera
Model:	WV-X8570N, WV-S8530N
Rating:	PoE DC 48V, 265mA (For Model WV-X8570N) PoE DC 48V, 210mA (For Model WV-S8530N)
Applicant Name and Address:	PANASONIC CORPORATION OF NORTH AMERICA PRODUCT SAFETY & COMPLIANCE DEPT TWO RIVERFRONT PLAZA 9TH FL NEWARK NJ 07102-5490 UNITED STATES

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared by: Yusuke Enokimura

Reviewed by: Katsuyuki Nishimura

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

- A. Authorization - The Authorization page may include additional Factory Identification Code markings.
- B. Generic Inspection Instructions -
 - i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
 - ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
 - iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

The products tested are Network Cameras for use outdoor or indoor environment.

For Outdoor Environment Models: WV-X8570N, WV-S8530N

The Network Cameras are supplied from Power of Ethernet (PoE standard IEEE 802.3af).

These products are intended for outdoor use and have not been evaluated for use in burglary and theft applications.

Input/Output Connector is intended to connect in indoor location.

Model Differences

Model WV-X8570N is basic model in this report.

Model WV-S8530N is similar to Model WV-X8570N except for Current Rating, Camera Resolution, External Interface.

Model WV-X8570N

Current Rating: 265mA, Camera Resolution: 8M Pixel, External Interface: Available

Model WV-S8530N

Current Rating: 210mA, Camera Resolution: 2M Pixel, External Interface: Unavailable

Technical Considerations

- Equipment mobility : stationary
- Connection to the mains : not directly connected to the mains
- Operating condition : continuous
- Access location : operator accessible
- Over voltage category (OVC) : OVC I
- Mains supply tolerance (%) or absolute mains supply values : No direct connection
- Tested for IT power systems : No
- IT testing, phase-phase voltage (V) : N/A
- Class of equipment : Class III (supplied by SELV)

- Considered current rating of protective device as part of the building installation (A) : Not connect to mains.
- Pollution degree (PD) : PD 2
- IP protection class : IP66
- Altitude of operation (m) : less than 2000
- Altitude of test laboratory (m) : less than 1000
- Mass of equipment (kg) : 2.68kg
- The product was submitted and evaluated for use at the maximum ambient temperature (Tma) permitted by the manufacturer's specification of: 60°C
- The product was investigated to the following additional standards: CSA/UL60950-22 1st edition - Equipment to be Installed Outdoors, IEC 60529, Edition 2.2 + Corr. 1:2013 + Corr. 2:2015, UL50E 1st Edition, C22.2 No. 94.2 1st Edition.
- The following are available from the Applicant upon request: Installation (Safety) Instructions / Manual
- The outdoor equipment/enclosure is: Type 4X Enclosure, IP rated IP66
- The outdoor equipment/enclosure was evaluated for use in an ambient range of: -40 °C to +60 °C,

Additional Information

The network camera is only intended for a connection to an ethernet or PoE network without routing to the outside plant.

Additional Standards

The product fulfills the requirements of: UL 60950-22 1st Edition, Revised 2007-04-23, CSA C22.2 No. 60950-22-07 1st Edition, IEC 60529, Edition 2.2 + Corr. 1:2013 + Corr. 2:2015

Markings and instructions

Clause Title	Marking or Instruction Details
Power rating - Ratings	Ratings (voltage, frequency/dc, current)
Power rating - Company identification	Listee's or Recognized company's name, Trade Name, Trademark or File Number
Power rating - Model	Model Number
Outdoor Enclosure Marking	"Type 4X Enclosure" on Rating Label
IP Code	"IP66" on Rating Label

Special Instructions to UL Representative

N/A

Production-Line Testing Requirements						
<u>Electric Strength Test Special Constructions - Refer to Generic Inspection Instructions, Part AC for further information.</u>						
Model	Component	Removable Parts	Test probe location	V rms	V dc	Test Time, s
N/A	--	--	--	--	--	--
<u>Earthing Continuity Test Exemptions - This test is not required for the following models:</u>						
WV-X8570N, WV-S8530N						
<u>Electric Strength Test Exemptions - This test is not required for the following models:</u>						
WV-X8570N, WV-S8530N						
<u>Electric Strength Test Component Exemptions - The following solid-state components may be disconnected from the remainder of the circuitry during the performance of this test:</u>						
N/A						
<u>Sample and Test Specifics for Follow-Up Tests at UL</u>						
Model	Component	Material	Test	Sample(s)	Test Specifics	
N/A	--	--	--	--	--	