

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents			
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence	
1.00 (3.0.10.0) Feb., '17						First production.			
1.01 (3.0.10.0) Mar., '17	C				x			Improved Camera information in Live window on Step2.	
					x			Fixed some duplicate items (Capture size, Device title, VMD alarm) in Step2 and Step3 of Recording setup. The items should be set in Step2, then either just review or deleted the duplicate items in Step3.	
					x			Improved that devices could be registered even if the Internet mode = "ON".	
					x			Improved WV-ASM200 Demo can be upgraded to WV-ASM300 Demo on same PC.	
					x		For WV-ASM300/CH only		
					x		Unable to register demo, LITE and upgrade license.	-	Fixed.
					x		Unable to change Mask duration at VMD search tab on WJ-NX400.	-	Fixed.
					x		WJ-ASM300 terminated unexpectedly by clicking "Set" button.	After changing the Display/Hide function to be "On" at the operation window in setup menu.	Fixed.
					x		On the "Sequence number" tab, the sequence number would not change from WV-CU950 to applicable sequence.	If the sequence number were set manually.	Fixed.
					x		On layout pattern switch panel, unable to display of default layout pattern replaced to be new even if a new layout pattern were replaced.	-	Fixed.
			x		Unable to run WV-ASM300.	It may occur on a certain PC only.	Fixed.		
			x		The camera picture set at the upper left of the group setting was displayed as a single picture.	Default screen = "multi-screen" Automatically provide full screen display of the operation window = "ON".	Fixed.		
1.02 (3.0.10.0) Apr., '17	C				x	-	-	Changed company name from Panasonic System Networks Co., Ltd. to Panasonic Corporation.	
					x	-	-	Improved for network adapter to be able to select in STEP 1 of easy setting, detailed setting.	
				x			CPU load may become high when using timeline function.	In a case many recorder are connected.	Fixed.
				x			Unable to transmit audio from WV-ASM300.	When authentication at audio setting of camera is set to ON.	Fixed.
				x			Unable to transmit audio.	In a case using a combination of Fisheye camera and Network microphone in Internet mode.	Fixed.
			x		Images to be transmitted even after exiting WV-ASM300.	-	Fixed.		

VER (ActiveX VER) Release Date	Priority Rank Level				Contents		
	A	B	C	U			
1.02 (3.0.10.0) Apr., '17	C			x	The following settings on WJ-NX400 became setting to the same setting values in synchronization with the On / Off setting of "Sub stream recording"; (1) Set frame rate for pre-event recording to the one for event recording. (2) No transmitting the bit rate setting to the camera with the same setting for basic setting, event recording, and emergency recording frame rate.	By setting transmission from WV-ASM300.	Fixed.
				x	On WJ-NV300, audio output setting of the monitor to selected "Selected camera" even if selecting Cam.2 - Cam.32.	By setting transmission from WV-ASM300.	Fixed.
				x	On H.265 cameras, camera picture rotated 180-degree.	By setting transmission from WV-ASM300.	Fixed (factory default value to be blanked).
				x	Unable to control Washer on WV-SUD638.	By System Controller WV-CU950.	Fixed.
1.03 (3.0.11.0) May, '17	C			x	WV-ASM300 crashed by attempting to register devices from "Initial setup" or "Advanced setup" while certain cameras (*) had been registered in MJPEG on WJ-NV300/NX400/ND400. *: WV-S1110, S1111, S1112, S1130, S1131, S1132, S1432, S1510, S1511, S1531, S2110, S2111, S2130, S2131, S2132, S2211, S2231, S2510, S2511, S2531, S2532, X6511 and X6531.	On firmware versions 1.01 and 1.02 of WV-ASM300.	Fixed.
				x	-	-	Supported WJ-ND400 version 5.60 and WJ-NV300 version 1.80.
				x	-	-	Deleted the "Save" button at "Step3 Setup transmission" in "Initial setup".
				x	Camera registration was not effected on recorders even if proceeding Step1 through Step4 and transmitted the setup.	Registered offline cameras in the recorder and saved once.	Fixed.
				x	Recording schedule 1 on WJ-NV300/NX400 would be restored to factory default for WV-ASM300 to transmit recording schedule.	If a recording schedule at Timetable2 in Recording schedule 1 on WJ-NV300/NX400 is exist.	Fixed.
				x	Timetable on WJ-ND400 would became abnormal.	One of the following cases; (1) When there was a mismatch in the time specified for the time zone 1-6 of each day. (2) There were four or more time zones of schedule or event. (3) When using program 4-8.	Fixed.
				x	Display images of the live window at the same position were switched if changing the display position by dragging and dropping on the operation window.	While displaying live window.	Fixed.
				x	Unable to receive "Start time & date" and "End time & date" of Summer Time (Daylight Saving Time) and Timeline.	When a table of Summer Time (Daylight Saving Time) was exist but turning off.	Fixed.
		x	Setting of "Upside-down" on WV-X6511 and WV-X6531 to be "OFF" by transmitting the setup.	When setting "Upside-down" = "ON" on WV-X6511 and WV-X6531.	Fixed. Note: It will be unable to select it.		

VER (ActiveX VER) Release Date	Priority Rank Level				Contents		
	A	B	C	U			
1.03 (3.0.11.0) May, '17	C			x	On WJ-NV300, changed the setting of "H.264" as compression method on Camera CH1 and CH2 to " MJPEG" by transmitting setup from WV-ASM300, unexpectedly.	Open the "Step3 recording setup" in "Advanced setup", then open "Recorder detail setup" in "Set recording event" and transmit setup.	Fixed.
				x	Changed the setting of "In-screen character display position" at "Camera detail window" in "Step2 Camera registration", unexpectedly. Or, transmitting setup may not effected on the settings.	-	Fixed.
				x	Playing back SD memory card may be done on the live monitor while it was in operation.	-	Fixed.
1.10 (3.0.12.0) July, '17	U			x	-	-	Supported WJ-NX200 version 1.02.
				x	-	-	Improved "Advanced setup" and "Camera detail setup" that are added "Image rotation" (0deg/90deg/180deg/270deg) setting function on STEP 2.
				x	-	-	Improved that "Advanced setup" could set "Smart coding /Gop control (On(Advanced))" on H.265 i-PRO EXTREME Series cameras with "Transmission priority" set to "Frame rate".
				x	-	-	Improved "System/Basic setup", "System/Drawing setup" and "System/GUI display setup" showing detail explanation by tooltip window.
				x	-	-	Improved dialog message for setting window that show "New settings are saved." when saving settings.
				x	-	-	Improved dialog message for setting window that showed warning message when you switched windows without saving configuration changes.
				x	-	-	Improved "Advanced setup" to always show the essential elements of the devices (IP address, port number and model number and so on) even if horizontal scroll operation were performed on the device list.
				x	-	-	Improved "Initial setup" that showed warning message* when you select STEP2 without available recorder. *(Warning message is "There is no recorder available for setup in the "Initial setup" page.")
				x	-	-	Improved "Advanced setup" that was able to register the devices by FQDN format in addition to IP address format.
				x	-	-	Improved "Advanced setup" that was able to register multiple devices with the same IP address/FQDN and having different port numbers.
				x	-	-	Improved "Thumbnail search" function which was added "120 min." option for "Display interval".
				x	-	-	Improved "Convert a file to the standard format" function supporting to convert from n3r(H.265) to mp4(H.264)/wmv.
		x	-	-	Added new function "Display video information". WV-ASM300 can show "Bit rate", "Receiving frame rate" and "Viewing frame rate" by overlay on the images.		
		x	-	-	Supported to change license from DEMO license to LITE license.		
		x	-	-	Changed the factory default value of "Panasonic" logo display preferences from OFF to ON.		
		x	-	-	Improved "download" function supporting autorun of the installs version of NXViewer that supplied in the CD-R or DVD-R.		

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
1.10 (3.0.12.0) July, '17 Added on Jul. 13,2017	C				x	-	-	Improved supporting smooth the high-speed playback on WJ-NX400/NX200.
					x	-	-	Improved NTP (Network Time Protocol) setting. At STEP1 in Advanced setup, when the time synchronization master is checked on a recorder, the other recorders set the IP address of the time synchronization master as the NTP primary server address. The check state of the time synchronization master is saved in the DB.
				x		Unable to set Adaptive black stretch. (No choice at Detailed setting in STEP2 showed a blank.)	-	Fixed.
				x		Changed not to use the stream 4 in the AUTO stream setting.	During H.264 streaming on H.265 camera.	Fixed.
				x		A popup window showed busy at STEP4 in online registration.	While saving the settings.	Fixed.
				x		Camera picture became solid black.	By selecting same camera with in playback within device tree.	Fixed.
				x		Unable to cancel the alarm action by right click menu.	In a case, Alarm camera direct live window is "ON" and Auto reset wait time is "Off".	Fixed.
				x		When switching the group on the live window side set for camera directive reception, the other live window became solid black picture.	When the live window 1 and the live window 2 are group-displayed with only the camera under the same recorder, one is via all recorders, the other on the camera direct setting.	Fixed not to be solid black picture.
				x		Unable to set Subnet mask/Default Gateway properly on IP address individual setup at STEP1 in Advanced setup.	-	Fixed.
					x	-	-	Improved that the icon names on map to be displayed depending on the choice of "Display of icon name on map".
				x		The icon side close to the selected icon may be selected.	When placing icons close to each other on the map monitor.	Fixed.
				x		CH information can not be correctly recognized on the WV-ASM 300.	When terminal alarm recording is set for cameras CH 65 and after by the recorder side.	Fixed.
				x		Changed settings such as the resolution of the camera by transmitting settings from the WV-ASM 300 made although none of the camera detailed setting in STEP 2 and setting change in STEP 3 were changed.	-	Fixed.
				x		Unable to select the fisheye display menu although even if it should be able to do.	When 360-deg camera and network microphone are linked.	Fixed.
		x		Unable to update the face search monitor's alarm or register face image.	Once exiting the WV-ASM 300 while the face search monitor is displayed, then starting up.	Fixed.		
			x	-	-	Changed the configurations for Panasonic Alarm Notification. - Not to set for Panasonic Alarm notification at Camera advanced setup in STEP2 when VMD Alarm="OFF". - It will be turned ON when the VMD alarm is ON if the notification destination of the original alarm is set. Or, it will be turned it ON, and the notification destination will be added at available place if it were not set. It is set to the notification destination 1 if there were no vacancy.		

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
1.10 (3.0.12.0) July, '17 Added on Jul. 13,2017	C					WV-ASM300 aborted by clicking "Setup" button at Camera setup on device registration window in the Master / Slave configuration of the WV-ASF 900.	-	Fixed.
					x	-	-	Changed the setting to 15 fps mode (previously 30 fps mode) when the imaging mode of the 4K camera is "8 megapixel".
				x		Unable to download recording stream 2 at acquiring log list from SD memory card.	-	Fixed.
				x		Aborted application software by moving window from Recorder detail setup in STEP3 of Advanced setup without save at STEP4.	-	Fixed.
				x		The application aborted.	When changing the Internet mode to ON from the edit screen for the newly detected recorder in STEP 1 of the Advanced setup.	Fixed.
				x		In the live window, the image would not recover even after network recovery if the picture was solid black due to network disconnection.	-	Fixed.
				x		The maximum screen number of the live window 2 to 4 became "-".	When converting the setting data of WV-ASM200 + WV-ASE201 + WV-ASE202 with the conversion tool, and loading only with WV-ASM300 (without WV-ASE 202).	Fixed.
				x		Failed transmission if checking connection for devices (added at offline) in STEP 1.	-	Fixed.
				x		The application aborted.	By switching the recorder to STEP 2 while the network disconnected.	
				x		Unable to associate WV-SFV781LH, WV-SPV781LJ and WV-SPV781LH with recorder.	-	Fixed.
			x	In the live window, unable to work Alarm camera direct live window.	After the events as follow; occurrence of Alarm camera direct live window by alarm occurrence, after exiting the live window without releasing the alarm, open the live window again.	Fixed.		
			x	Unable to work Alarm camera direct live window.	By activating the live window after an alarm has occurred on the operation window.	Fixed.		
			x	-	-	Changed not to display the version information of STEP 4 for devices added offline.		
1.20 (3.0.14.0) Sept., '17	C			x	-	-	Supported WJ-NX200 Version 1.11 - New cameras (WV-S6110, WV-S6111, WV-S6130, WV-S6131 and WV-S6530N) - Network microphone, Model WV-SMR10 - Network Microphone registration and camera registration on WJ-NX200 by WV-ASM300 - Download in MP4 - Audio codec (AAC)	

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
1.20 (3.0.14.0) Sept., '17	C				x	-	-	Supported WJ-NX400 Version 1.11 - New cameras(WV-S6110, WV-S6111, WV-S6130, WV-S6131 and WV-S6530N)
					x	-	-	Supported new cameras(WV-S6110, WV-S6111, WV-S6130, WV-S6131 and WV-S6530N).
					x	-	-	Added settings (would not setup nor device setup for WJ-ASM300 which downloaded the device information) related to the device management in Setup.
					x	-	-	Added a settings if displaying frame of camera range in the settings related to map.
					x	-	-	Added a mode not displaying thumbnail images in the settings related to map.
					x	-	-	Added displaying a message indicating that rebooting is required when setting was saved for the screen but not to be reflected immediately (items requiring application restart).
					x	-	-	WV-ASE232W (Extension software for POS) has supported WJ-NX200.
					x	Unable to load the setting data with displaying an error of excess number when attempting to load setting data of 130 recorders even though there was the license of WV-ASE203.	-	Fixed.
					x	No map displayed when logging in as a normal user.	Converting MAP and user set data with ASM 200, loading with ASM 300, responding to the problem that MAP is not displayed when logging in as a normal user.	Fixed.
					x	Increased the number of groups unexpectedly by loading the setting data of the group.	In case the data created on version 1.03 and loading on version 1.10.	Fixed.
			x	Unable to set fog compensation even if the level adjusted to a value other than minimum.	-	Fixed.		
			x	A face frame may be displayed regardless of face frame display setting being off.	When registering or changing the setting and saving the setting by basic setting or device related setting - device registration.	Fixed.		
1.21 (3.0.14.0) Oct., '17	A			x	The license information of WV-ASM300 might be cleared on a PC.	When it is upgraded from the older versions of OS to Windows 10, or when Windows Update on Windows 10 is applied to it	Fixed.	
1.30 (3.0.19.0) Jan., '18	C				x	-	-	Supported WJ-NX200: Firmware version 2.0 (and later) - Supported WV-V series cameras - Supported WV-S4150, WV-S4550L and WV-S4550LM
					x	-	-	Supported WJ-NX300.

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
1.30 (3.0.19.0) Jan., '18	C				X	-	-	Supported WJ-NX400: Firmware version 2.0 and 2.1 (and later) - WV-V series cameras - Network Microphone WV-SMR10 - Registration network microphone and registering cameras from WV-ASM300. - Downloading MP4 function. - Advanced Audio Codec (AAC) - WV-S4150, WV-S4550L and WV-S4550LM [WJ-NX400 must be firmware version 2.1 (and later).] - Failover function with displaying its status by icon - HDD stand-by control mode.
					X	-	-	Supported new firmware on WJ-NV300 and WJ-ND400; - New cameras: WV-S6110,WV-S6111,WV-S6130,WV-S6131,WV-S6530N
					X	-	-	Supported Concurrent User License Kit, Model WV-ASM300CLW (sold separately).
					X	-	-	H.265 hardware decode.
					X	-	-	Added choices of Panorama / Double Panorama onto type of image display selection in fisheye.
					X	-	-	Improved as follow on Single PTZ/Quad PTZ display selection in fisheye; - Smooth display of pan / tilt display - Improved the electronic wheel zooming operation of the fixed camera so that the operation feeling is the same as when operating the fixed camera directly even if the zoom magnification changes. - Fisheye control made resizable
					X	-	-	Improved the blank user name/password input fields colored to be colored so as to make it highlighted on Setup (Initial setup, Advanced setup, Device registration) in Setup windows.
					X	-	-	Improved the camera icon size on the map monitor can be changed to 25%, 30%, 50%, 75%, 100% (original size).
					X	-	-	Improved the number of devices that can be registered and the number of registered devices could be displayed in po-up help on the device list screen of the device setting (Initial setup, Advanced setup, Device registration) on the Setup windows.
					X	-	-	Changed "Model no." at STEP2 of Device list in Camera detail setup window to "Device title".
					X	-	-	Changed "Display/show" button at Function panel in operation window to "Display the panel open/close" button.
					X	-	-	Improved to return to the maximized screen that was returning to the normal screen by the [Back] operation after shifting from the maximized screen to the full screen.
			X	-	-	Improved to be able to back by "ESC" key on the full screen.		
			X	-	-	On the camera setting screen under the recorder displayed from the "Registered device" of "Setting device" in "Settings screen", improved "Stream type" and "Internet mode (over HTTP)" to be collectively configurable.		

VER (ActiveX VER) Release Date	Priority Rank Level				Contents			
	A	B	C	U				
1.30 (3.0.19.0) Jan., '18	C			x	Unable to playback (Solid black picture or still picture)	After transitioning from the live display of the 25/36/49/64-screen to the 1-screen, playback, thereafter the special playback such as high speed playback and when the playback button is pressed in order to return to the normal speed.	Fixed.	
				x	Unable to end sequence by right click on mouse.	While in 16-screen and 3 sec. sequence mode.	Fixed.	
				x	Panasonic alarm protocol on recorder to be "ON" even if saving and sending the one to be "OFF" at Timetabel1 of Schedule1, Recording schedule, "Recorder detail setup" of "Step3 Recording setup" in "Advanced setup". (Target recorders: WJ- NV300, WJ-NX400 and WJ-NX200.)		Fixed.	
				x	Schedule recording to be "ON" even if saving and sending the one to be "OFF" at Timetabel1 of Schedule1, Recording schedule, "Recorder detail setup" of "Step3 Recording setup" in "Advanced setup". (Target recorders: WJ-NX400 and WJ-NX200.)	-	Fixed.	
				x	WV-CU950 did not work.	When logging in again after logging out once at WV-ASM 300.	Fixed.	
				x	Switching Sound collection position ON and OFF, repeatedly.	By pressing Sound collection position ON/OFF repeatedly.	Fixed.	
				x	Possible to hear audio while muting Mic input.	By change settings on the setting screen while Mic input muted.	Fixed.	
				x	In the live monitor, the camera of "live acquisition via the recorder" may become a black picture during the sequence.	When groups of "camera" and "recorder" are mixed in live acquisition destinations of cameras under WJ-NX400K and WJ-NX200, depending on the combination method (Example: one group = cameras only, the other group = recorders only)	Fixed.	
					x	-	-	Improved reliability for WV-ASM300 not to be able to restart or needed to re-install OS.
					x	In the live monitor, black image appeared and would not return to the normal image when a forced logout due to recorder setting change occurs.	-	Fixed.
Added on Jul.25,2018							Changed the system of correction display mode of single and 4-screen PTZ.	
1.31 (3.0.19.0) Feb., '18	C			x	Latest alarm on the day may not be listed at the top of the alarm log list.	After upgrading software.	Fixed.	
				x	25-screen or more may not be displayed properly.	When register WV-ASE 202 license and display more than 25 images.	Fixed.	
				x	Unable to output audio of certain cameras; - 6 series (WV-SFV/SFR/SFN/SPN/SPW6 series) - 5 series (WV-SFV/SFR/SFN/SPN/SPW5 series) - 3 series (WV-SFV/SFR/SFN/SPN/SPW3 series) - 1 series (WV-SFV/SFN1 series)	Import setup data that was saved on the older version right after (no cameras registered) installing or upgrading version 1.30 on a PC. When install version 1.30 on new PC and import the setup data that was saved on the older version.	Fixed.	
Corrected on Feb.2,2018								

VER (ActiveX VER) Release Date	Priority Rank Level				Contents			
	A	B	C	U				
1.33 (3.0.19.0) Mar., '18	Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)				Contents Issue (Phenomenon) Occurrence condition Correspondence			
	C		x			Displayed black images on the PC at a certain conditions and send unnecessary commands to the network recorder continuously.	When satisfying all of the following; - Display camera pictures of both connected camera(s) and unconnected camera(s) in multi-screen. - Display the image of the camera registered in the recorder on multi-screen. - Set "Live image source" of the unconnected camera to "camera" (Connected camera became unconnected state after setting in connected state). - Start playing back again right after playback start, stop, and stop on multi-screen. When a certain period of time has elapsed without any other operation thereafter.	Fixed.
1.37 (3.0.19.80) Apr., '18	C			x	Picture may not be displayed while setting alarm action.	-	Fixed.	
				x	Operation may become unstable by switching live monitor ON and OFF repeatedly.	-	Fixed.	
				x	Registered camera information may not be saved correctly. As a result, unable to operate camera properly.	-	Fixed.	
				x	Live monitor screen may flash.	-	Fixed.	
				x	Icons on the map monitor, names, etc. may not be displayed correctly.	-	Fixed.	
				x	The timing of turning on the recording lamp may be different between the operation monitor and the live monitor.	-	Fixed.	
					x	-	-	Improved the smoothing of the operation at the start and end of the split screen display.
				x	License information may be in an incorrect state due to version upgrade of Windows OS.	-	Fixed.	
				x	Setting of "Image display method" in "GUI display setup" may become "OFF".	-	Fixed.	
				x	Setup file converted from WV-ASM200 to WV-ASM300, may not load properly.	-	Fixed.	
1.40 (3.0.19.80) May, '18	C			x	-	-	Supported new cameras; WV-X4571L(M), WV-X4171, WV-X4170	
				x	-	-	Supported new cameras: WV-X4571L and WV-X4171 Supported new firmware: WJ-NX400 Ver2.2, WJ-NX300 Ver2.2 and WJ-NX200 Ver2.2	
				x	-	-	Supported new cameras: WV-X4571L(M), WV-X4171, WV-X4170, WV-S4550L(M), WV-S4150 *H.264/M-JPEG only Supported new firmware: WJ-NV250 Ver2.10, WJ-NV300 Ver2.10 and WJ-ND400K Ver5.90	

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
1.40 (3.0.19.80) May, '18	C				x	-	-	Added a choice of log-in password policy for WV-ASM300 that it must include at least 3-type of characters among the 4-type as follow; [1] Alphabetic characters (uppercase letters) [2] Alphabetic characters (lower case), [3] Numbers, [4] Symbols (*) *: Symbols ~!@#\$%^&*()_+ \}{}[<>.,/?`
					x	-	-	Improved that log-in failure of WV - ASM 300 would be logged.
					x	-	-	Improved to be able to set camera preset position and name for AUX.
					x	-	-	Improved to display a warning dialog while activating IP easy setting software at the time of device registration.
					x	-	-	Changed labeling of setting menu from "System - Drawing setup" to "System - Drawing and audio setup".
					x	-	-	Changed displaying a dialog window to confirm changing device settings at initial setup process.
					x	-	-	In live image display via recorder and same number of strokes during sequence, changed displaying a black picture in the case of failure to communication with a camera.
					x	-	-	Improved not to display groups of 25 or more images not displayed in the step list of the sequence setting screen.
					x	-	-	When concurrent access license is used, when it logs on to unregistered recorder, it responds to display message "The designated recorder is not covered by the concurrent user license."
					x	-	-	Improved the transition of video smoothly at the start and end of the full screen display.
					x	-	-	Improved to be unable to set blank for port number when slave mode is selected in timeline setting.
1.41 (3.0.23.0) June, '18	C				x	Ended WV-ASM300 abnormally, and the screen display may be distorted during termination or the next startup.	By terminating the application from the task bar during displaying the live monitor - map monitor in the window.	Fixed.
					x	Unexpected command alarm to be sent.	-	Fixed.
					x	-	-	Supported Digest authentication between WV-ASM300 and cameras.
1.41 (3.0.23.0) June, '18	C				x	-	-	Supported new firmware: WJ-NX400 Ver2.2, WJ-NX300 Ver2.2 and WJ-NX200 Ver2.2 Added choice of "Digest or Basic" at Authentication method between recorders and cameras.
					x	Continuously clicking the buttons around the control pad of camera operation panel, may be a cause of continue panning / tilting.	-	Fixed.
1.42 (3.0.25.0) Aug., '18 Except WV- ASM300/CH	C				x	-	-	Supported new cameras; WV-X8570N and WV-S8530N. Added a screen pattern used for the group display exclusive for new cameras.
					x	-	-	Supported new cameras; WV-S1550L(N),WV-S2550L(N) and WV-2250L.

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
1.42 (3.0.25.0) Aug., '18 Except WV- ASM300/CH	C				x	-	-	Supported new components; WJ-NX400 V2.3, WJ-NX300 V2.3 and WJ-NX200 V2.3 - Supported new cameras; WV-X8570N, WV-S8530N, WV-S1550L(N),WV-S2550L(N) and WV-2250L
					x	-	-	Supported new components; WJ-NV300 V2.20 - Supported new cameras; WV-S1550L(N), WV-S2550L(N) and WV-2250L *: H.264/M-JPEG only
					x	-	-	Supported Facial Recognition Server Software, WV-ASF950.
					x	A frame dropped in the picture and a break in the sound occurred. A frame dropped in the picture on 360-degree cameras, and a break in the sound occurred on 360-degree cameras linked with Network Microphones.	When the 360-degree camera performs Single PTZ / Quad PTZ display with distortion correction display and PTZ operation.	Fixed.
					x	Registered face image only in the first master server even if face image registration were registered as master servers wile using WV-ASE231W.	Registered a face image from the face search result, and a plurality of WV-ASF900s are registered as a master server.	Fixed.
					x	Exception error of .NET Framework may occur.	By notifying the event of camera disconnect / restore from the recorder in the setting with the device error log display off.	Fixed.
					x	Unable to zoom operation until making click centering once when multi-screen display of 360-degree camera with Single PTZ display.	-	Fixed.
1.50 (3.0.26.0) Aug., '18	C				x	-	-	Supported WJ-NV300 V2.20. - Supported new cameras on H.264/M-JPEG only; WV-S1550L,WV-S2550L and WV-2250L
					x	-	-	Supported WJ-ND400 V6.00. - Supported new cameras on H.264/M-JPEG only; WV-S1550L,WV-S2550L andWV-2250L
					x	Single and 4-screen of 4:3 images on WV-SF438,WV-SW458 may become stretched outwards by correcting.	On firmware versions 1.30 through 1.42.	Fixed.
1.51 (3.0.26.0) Sept., '18	B				x	Operation may not be able to done by scrolling face search result at Face search tab of Face search monitor function, repeatedly.	While using with WV-ASE231W.	Fixed.
					x	Display only 100 registered faces (from old one) instead of displaying up to 1,000 registered faces, and unable to edit the 101th and newer registered faces (no problems on 101th and newer face matching alarm notifications).	1. On version 1.42 and 1.50 2. Using with WV-ASE231W and WV-ASF900. Note: Nothing problem combination with WV-ASE231W and WV-ASF950.	Fixed.
1.60 (3.0.28.10) Dec., '18						-	-	Supported new cameras; WV-S3131L, S3531L, S3111L and S3511L
						-	-	Supported WJ-NX400 V2.4, WJ-NX300 V2.4 and WJ-NX200 V2.4 - Supported new cameras: WV-S3131L, S3531L, S3111L and S3511L

Revised on Aug.1, 2018

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
1.60 (3.0.28.10) Dec., '18	C				x	-	Supported WJ-NV300 V2.30 and WJ-ND400 V6.10 - Supported new cameras: WV-S3131L, S3531L, S3111L and S3511L *: H.264/M-JPEG only	
					x	-	For the device in the initial state, supported new password policy on recorders that must include at least 3 types of characters among "upper case letters / lower case letters / numbers / symbols".	
					x	-	Added a function to capture the camera titles which defined on recorders by downloading the device information.	
					x	-	For WV-SF438 and WV-SW458, added setting menu "Single PTZ/Quad PTZ display format for fisheye image (3M fisheye camera)" to select a correction method for when displaying fisheye images received from 3M fisheye camera in the single PTZ display or in the quad PTZ display. - Entire image correction: Method that averagely corrects distortion of an entire image. - Center part correction: Method that mitigates distortion especially around the center of an image. Peripheral edges of image will be displayed distorted when compared with the entire image correction."	
					x	-	Improved switching screen smoothly by displaying no images and indicating an icon that screen transition is in progress while switching to full screen display.	
				x		Displaying either solid black screen or still image continuously while in the same number of screen sequence, and "Maximum concurrent access error" may occur.	-	Fixed.
					x	Solid black picture may be displayed while in sequence mode and unable to restore.	In a case, the sequence mode with the same number of screens, the same camera placed on the same divided screen.	Fixed.
					x	Unable to display multi-screen for the cameras under the Video Insight Server.	While using WV-ASE306W, Video Insight Server Registration License for ASM300.	Fixed.
					x	The application software may abort by selecting a camera under the Video Insight Server.	While using the Extension Software WV-ASE306(W),	Fixed.
					x	Unable to run WV-ASM300 due to ".net framework 4.6" may not be installed.	If Windows 8.1 were; One of German, French, Italian, Spanish or Russian language. Or, If Windows 7 were; ".net framework 4.0/4.5" in one of German, French, Italian, Spanish or Russian language, has been installed.	Fixed.
			x	Unable to select compression method on WV-NS95x, WV-NW96x or WV-NP100x which was (were) registered under WJ-ND400.	After changing the "Live image source" to be "Camera".	Fixed.		
			x	Retrieve the setup data may be failed.	In a case, WV-ASM300 were firmware version 1.30 or later and the setup data were saved under firmware version 1.20 or earlier.	Fixed.		

VER (ActiveX VER) Release Date	Priority Rank Level				Contents				
	A	B	C	U					
1.61 (3.0.28.10) Dec., '18	C			x	When using WV - ASE 231 W, face images managed by slave servers may not be displayed.	When the WV-ASF 950 has a master / slave server configuration and encryption function is enabled	Fixed.		
				x	When WV-ASE 231W is used, the names and remarks of the second and subsequent real-time alarms may not be displayed correctly.	When WV-ASF 950 has multiple master server configuration and each server has encryption function enabled with different key	Fixed.		
				x	All images may become solid black images for a while.	By selecting an area not assigned to the camera during multi-screen playback and right-click.	Fixed.		
				x	On WV-ASM300 Ver V 1.60 or earlier, saving settings more than once may not be saved correctly after the second time.	-	Fixed.		
					x	-	-	Improved so that streams (3) and (4) of WV-SFV781 / SPV781 can be selected.	
1.70 (3.0.28.10) Apr., '19	C			x	-	-	Added new mode to change the map image display magnification (100%, 200% and 300%).		
				x	-	-	Added new camera icon sizes (90%,80%,60%,45%,40% and 30%) can be changed for each map.		
				x	-	-	Improved the camera icon position conversion accuracy on the map when converting the setting data of WV-ASM200 using the converter tool.		
				x	-	-	Added sort function and manual sort function of tree in group, sequence, map and folder setting screen.		
				x	-	-	In order to prevent malfunction, added "Tab separation" setting to "System"->"Basic settings" and added a mode that can not separate tabs.		
				x	-	-	Added a function (expansion method) selection function of WJ-NX400, NX300, and NX200 (V2.50) that enables downloading of n3r format recording data exceeding 2 GB by automatic division.		
				x	-	-	Added the information as follow on the alarm notification message window in face search server. - "Category color" and "category name". - "Remarks" in the tool tip when the mouse cursor is placed.		
				x	-	-	Added "Name" and "Remarks" into the output details of people search in HTML file.		
				x	-	-	The start monitor set group / sequence may not work.	When the live monito is tabbed.	Fixed.
				x	-	-	Loading data which contains a custom icon set on the map may fail.	-	Fixed.
		x	-	-	Substream playback may return to the main stream by making special playback (such as high-speed playback, etc.).	-	Fixed.		

VER (ActiveX VER) Release Date	Priority Rank Level	Priority Rank Level				Contents		
		A	B	C	U	Issue (Phenomenon)	Occurrence condition	Correspondence
1.70 (3.0.28.10) Apr., '19	C			x		Recorded images may not be able to save normally by selecting MP4 format for downloading if all the following conditions were true: - One hour or more in the date and time range. - Files will be divided into multiple due to large image size. - Change a name of a download file by selecting "Rename".	-	Fixed.
					x	-	-	Supported new cameras; WV-S6532LN, WV-X6533LN, WV-S1570L, WV-S2270L and WV-S2570L
2.00 (3.1.2.0) June, '19	C				x	-	-	Supported new firmware version on recorders; WJ-NX400K, WJ-NX300 and WJ-NX200 WV-NX400K, WV-NX300 and WV-NX200 Firmware Version 3.00
					x	-	-	Added a function to take over the previous setting information by the "Download of device information" button when replacing a registered recorder or camera. Note: Not available to check connection for the device if it registered by the advanced settings (offline).
					x	Playback may not start after date selection on the Quick Playback panel of the operation monitor.	-	Fixed.
					x	Updating the status of the status bar (ex. Playback mark at the start of playback) may be slow in an environment of alarms occur frequently.	-	Fixed.
					x	-	-	Improved to allow user authentication even for groups other than the primary group when making user authentication using with an LDAP server (Microsoft Active Directory server). Also improved the information display at login window.
					x	Missing display the underscore of the first character of user name, the group name of registered LDAP server (Microsoft Active Directory server).	-	Fixed.
2.10 (3.1.2.0) July, '19	U				x	-	-	Supported a new function, Unregistered Face Detection, on WV-ASF950 Ver2.00.
2.11 (3.1.3.0) Sept., '19	C				x	Settings related to the user management might be initialized by loading the setup data.	When satisfying all of the followings: - The version of WV-ASM300 installed on the PC for the first time was either 2.00 or 2.10. - The setup data loaded for the first time with WV-ASM300 was version 1.61 or earlier.	Fixed.
2.20 (3.1.3.0) Oct., '19	C				x	-	-	Changed company name; from "Panasonic Corporation" to "Panasonic i-PRO Sensing Solutions Co., Ltd."
					x	-	-	Supported new System Controller, Model WV-CU980 firmware version 1.00.
					x	-	-	Added a function to create a dedicated group for each user.

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
2.20 (3.1.3.0) Oct., '19	C				x	-	-	Improved so that the display order of the camera list displayed on the menu panel of the map monitor can be changed.
					x	-	-	Improved so that the display/non-display of the map monitor camera icon and the name of map icon can be set individually.
					x	-	-	In high-speed playback smooth mode, improved by adding a choice of priority either playback speed or frame rate.
					x	-	-	Addressed known vulnerabilities.
				x		WV-ASM300 terminated abnormally.	When using the .NET Framework 4.8 and combining the operation monitor as a tab with a still image displayed on the VMD search screen or thumbnail search screen separated in a separate window.	Fixed. Please refer to the Operating Instructions, "4.5.Use the search window"
						Added on Dec 13, 2019	Improved the behaviors when switching to 1-screen display and then switching the camera, after switching a camera in any single screen in multi-screen mode with System Controller WV-CU950 as follows. - So that the image selection frame to be placed at the original position when switching back to multi-screen display. - Not to change the order of screens after switching cameras.	
2.21 (3.1.3.0) Dec., '19	C				x	-	-	Supports WJ-NX400K, WJ-NX300 and WJ-NX200 V 3.10
					x	-	-	Changed the company name of NX Viewer; from "Panasonic Corporation" to "Panasonic i-PRO Sensing Solutions Co., Ltd."
				x		Converting the n3r file downloaded from the NX-series recorders (WJ-NX400K, WJ-NX300 and WJ-NX200) to the standard format may fail.	-	Fixed.
			x	The administrator registration window may appear again even if the administrator account has been registered on the same window after the license registration.	-	-	Fixed.	
2.30 (3.2.2.0) April, '20	B				x	-	-	Supports new cameras: WV-U1132, WV-U1142, WV-U2132L, WV-U2142L, WV-U1532L, WV-U1542L, WV-U2532L, WV-U2542L, WV-U1130, WV-U2130L, WV-U2140L, WV-U2530L, WV-U2540L
					x	-	-	Supports new firmware version 3.20 of WJ-NX400K, WJ-NX300 and WJ-NX200.
					x	-	-	Added 3D dewarp function for fisheye images.
					x	-	-	Improved to be able to assign other optional functions available only with the operation window of ASM300 to the below function keys and buttons of the system contraller WV-CU980: - Function keys (F1 toF10) - [A] button, [B] button and Top button of the joystick unit

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
2.30 (3.2.2.0) April, '20	B				x	-	-	Improved to be able to move the image selection frame on the operation window using the system contraller WV-CU950 or WV-CU980.
					x	-	-	Improved to display all groups on the setting screen of "Displayable group" in "User setup". (In the previous versions, the displayable groups are limited to the groups with screens up to the number set in "Operation window (multi-screen) with the maximum number of areas".)
					x	-	-	Added "Cancel all" button to deselect all the listed items on the setting windows of "Displayable camera", "Displayable group", "Displayable sequence" and "Displayable map" on the "User setup" page.
				x		Unable to launch WV-ASM300 with "ASDB Service failed" error. (Occurrence frequency: Low)	When installing and launching WV-ASM300 for the first time (Note: This issue does NOT occur with reinstalling such as version upgrade)	Fixed.
				x		-	-	Changed the communication timeout values for the communication with Facial Recognition Server Software WV-ASF900 and WV-ASF950 listed below from 10 minutes to 30 seconds. - "Alarm notification" window display - "Alarm search" window display - The statistic results of age, gender and head count for each camera display) (Inoperable time will be shortened by this change.)
				x		-	-	Changed the method of Keep-Alive monitoring between WV-ASM300 and Facial Recognition Server Software WV-ASF900 and WV-ASF950 to reduce the load of the facial recognition servers.
			x			The 129th and later cameras, registered on Facial Recognition Server Software WV-ASF900 or WV-ASF950, cannot be registered on WV-ASM300. (Occurrence frequency: High)	-	Fixed.
		x		WV-ASM300 may skip to the next recorded image of a camera although WV-ASM300 should display a black screen for the unrecording period of the camera. (Occurrence frequency: High)	Under all the conditions below: - Multi-screen display such as 9-screen with the resolution of SXVGA or wider - When the number of cameras displaying image is smaller than the number of split screens (This issue does NOT occur when there are many images not shown as black screens) - When recording with high frame rate such as 30 fps - When displaying the images recorded with a WJ-NX Recorder(NX400K, NX300 or NX200) in multiple display.	Fixed.		

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
3.00 (3.2.5.0) June, '20	C				x	-	Supports new cameras: WV-X1551LN, WV-X2551LN, WV-X2251L	
					x	-	Supports new firmware version 4.00 of WJ-NX400K, WJ-NX300 and WJ-NX200.	
					x	-	Supports cameras with WV-XAE200W(AI-VMD). Supports WV-XAE200W(AI-VMD) and i-VMD with the following items. 1. Added the screen for setting the name of the AI-VMD/ i-VMD alarm (Intruder/ Loitering/ Direction/ Cross line). 2. The alarm names above will be applied in the following screens. - Alarm type in the [Setting]> [Event]> [Alarm action] tab> [Alarm linkage registration] window - AI-VMD/i-VMD(HD600) items on the [Search]> [REC event search] tab - Alarm log contents in [Setting]> [Maintenance]> [Application Log] tab - The contents in alarm notification message 3. Added "Intruder", "Loitering", "Direction", "Cross line", "OBJECT ALARM (left behind/removal)" to "Alarm type" in the [Alarm linkage registration] window. 4. Added "Intruder", "Loitering", "Direction", "Cross line" to the AI-VMD alarm search by conditions for REC event search of NX-series recorder	
					x	-	Supports cameras with WV-XAE201W(AI Privacy Guard). - Added the menu to switch between AI privacy guard image and the normal image to the pop-up menu of the operation window. - Added the "AI privacy guard image switching" function for switching to the normal image without AI privacy guard, to the [User level setup] tab in [User management]. - Added icons of cameras with AI privacy guard	
					x	-	Improved to be able to search and display all the face images by clicking the page turn button even if the number of search results is large, as older versions do not search up to the last face image in the designated search range in this case. (WV-ASF950 needs to be version 2.20 or later)	
					x	-	Changed to display AVMD frame and tracks without adding the license of WV-ASE231.	
					x	AVMD frames and tracks may be displayed when displaying images on a multi-screen. Note: AVMD frames and tracks are supposed to be displayed only when displaying images on 1-screen. (Occurrence frequency: High)	When all 3 conditions below are met: - WV-SAE200W is installed on the camera - The license of WV-ASE231 is added to WV-ASM300 - The camera in use supports cropping mode	Fixed.
					x	The screen may not switch to the live image from the camera in which an alarm occurred. (Occurrence frequency: High)	When all 3 conditions below are met: - when receiving an alarm from a panoramic camera - "On" is selected for [Additional alarm data] in the camera setting - The camera is registered as a stand-alone camera	Fixed.
			x	The preview image of the camera may not be displayed on the [Step2 Camera registration] window in [Device setup]> [Advanced setup].	When "Digest" is selected in [Authentication] for accessing the camera in the recorder setting.	Fixed.		

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
3.00 (3.2.5.0) June, '20	C			x		The position of AVMD frame and track on the image of WV-ASM300 may be misaligned compared to the camera browser image when "90 °" or "270 °" is selected for "Image rotation" in the camera setting.	When all 3 conditions below are met: - WV-SAE200W is installed on the camera capable of selecting "90 °" or "270 °" for [Image rotation] - The license of WV-ASE231 is added to WV-ASM300 - Operating with the image rotated	Fixed.
					x	-	-	Changed the name of WV-ASF900 and ASF950 from "Face Search Server" to "Facial Recognition Server" on the screen and the operating instructions of WV-ASM300.
					x	-	-	Changed the default port number to "80" of WJ-HD616 or WJ-HD716 for the setting of "ASM300 camera title", "Camera type" and etc.
					x	1. Unable to change the setting of "Live image source" on the [Camera setup] window in [Device setup] when WJ-NT304 or NT314 is registered in WJ-ND400. 2. Unable to display the image on WV-ASM300 when WJ-NT304 or WJ-NT314 is registered in WJ-ND400 with MPEG-4 selected for [Compression]. (Occurrence frequency: High)	-	Fixed.
3.10 (3.2.5.0) Sep., '20	C				x	-	-	Supports new cameras: WV-X1571LN, WV-X2271L, WV-X2571LN
					x	-	-	Supports new firmware version V4.10 of WJ-NX400K, WJ-NX300, WJ-NX200
					x	-	-	Added search by category function to the [Alarm search] tab on the face search window. Note: Available after upgrading facial recognition server WV-ASF950 to V3.00 or later
					x	-	-	Added the [Quick registration] button to the [Alarm], [Alarm search], and [Face search] tabs to improve the operability.
					x	-	-	Added the [Suitable example] button to the "Face image Evaluation" window for the reference of applicable or not applicable images to improve the operability.
					x	-	-	Added alarm icons to the "Select area" window to clarify the target for alarm, regardless of detection mode (Registered face/ Unregistered face detection) to improve the visibility.
					x	-	-	Improved the "Face image Evaluation" window to display "Recommended width of face" and "Detectable width".
					x	-	-	Added scroll bar to the face search monitor so as to improve the operability on a low-resolution monitor (1280x800 or lower).
			x	-	-	Improved the "List of registered faces" window so that it can be moved behind other screens.		

VER (ActiveX VER) Release Date	Priority Rank Level				Contents		
	A	B	C	U			
3.10 (3.2.5.0) Sep., '20	C			x	<p>- WV-ASM300 performs auto login even after logging out. Expected behavior: Displays login window</p> <p>- WV-ASM300 reboots and performs auto login even after terminating it when auto login is enabled. Expected behavior: Performs normal termination (Occurrence frequency: High)</p>	<p>When all the conditions below are met:</p> <ul style="list-style-type: none"> - Auto login is enabled - Displaying 2 or more live monitors on the separated windows - All of the live monitors are operated in the sequence display 	Fixed.
				x	<p>WV-ASM300 reboots and displays login window even after terminating it. Expected behavior: Performs normal termination (Occurrence frequency: High)</p>	<p>When both of the below conditions are met:</p> <ul style="list-style-type: none"> - Auto login is NOT enabled - Displaying 2 or more live monitors on the separated windows - All of the live monitors are operated in the sequence display 	Fixed.
					x	-	-
4.00 (3.2.6.0) Dec., '20	U			x	-	-	Supports new cameras: WV-X6533LNS, WV-S6532LNS, WV-S1572L, WV-S2572L, WV-S2272L, WV-S1552L, WV-S2552L, and WV-S2252L
				x	-	-	Supports new firmware version 4.20 of WJ-NX400K, WJ-NX300, WJ-NX200
				x	-	-	Enables "High-speed playback smooth mode" during high-speed playback of 3D Dewarp images with a reduced frame rate.
				x	-	-	Enables "Frame playback [NEXT IMAGE]" and "Reverse frame playback [PREV IMAGE]" functions for JPEG images of 3D Dewarp.
				x	-	-	Improved the operability of the windows for settings relating to the device management by adding "--" to the batch setting pull-down menu.
				x	-	-	Improved the visibility on the windows for settings relating to the device management by displaying busy cursor while processing, after changing the settings with the batch setting pull-down menu.
				x	-	-	Improved the functions for communicating with recorders to use HTTP/HTTPS as a communication method. Supported recorders and version: WJ-NX400K, WJ-NX300, WJ-NX200 / Version 4.20 or later
			x	-	-	Changed the default setting of [n3r file download method (NX series)] in [System]-> [Basic setup], from "Standard" to "Extension".	

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence
	A	B	C	U			
4.01 (3.2.6.0) Jan., '21	C			x	<p>WV-ASM300 displays the error notifications from the recorder(Panasonic alarm protocol notification) incorrectly as below:</p> <ul style="list-style-type: none"> - "VIDEO LOSS" incorrectly displayed as "Direction" - "FAN ERROR" incorrectly displayed as "Intruder" - "THERMAL ERROR" incorrectly displayed as "Loitering" <p>Screens with this issue:</p> <ul style="list-style-type: none"> - "Device error log" on the function panel - "Device error log" displayed in [Setting]-> [Maintenance]-> [Application log] <p>(Occurrence frequency: High)</p>	<p>When the below errors occur in the recorder/ encoder registered in WV-ASM300 version 3.00, 3.10, or 4.00:</p> <ul style="list-style-type: none"> - "Video loss" of WJ-GXE100/WJ-GXE500 - "Video loss" of WJ-HD616/WJ-HD716 - "FAN warning" and "Thermal error warning" of the recorder 	Fixed.
				x	<p>The setup data is initialized.</p> <p>(Occurrence frequency: High)</p>	<p>When satisfying all the conditions from "a" to "c" in Case1 or Case2.</p> <p>[Case1]</p> <ul style="list-style-type: none"> a. The version of WV-ASM300 initially installed on the PC is either 2.00 or 2.10. b. The setup data initially loaded into the WV-ASM300 is version 1.61 or older, including converted data from WV-ASM200. c. The WV-ASM300 has been upgraded to V2.20 or later. <p>[Case 2]</p> <ul style="list-style-type: none"> a. The version of WV-ASM300 initially installed on the PC is either 2.00 or 2.10. b. The setup data initially loaded into the WV-ASM300 is version 1.61 or older, including converted data from WV-ASM200. c. The setup data from the above WV-ASM300 has been loaded into another WV-ASM300 V2.20 or later. 	Fixed.
				x	<p>The logs filed in the following screens are deleted.</p> <ul style="list-style-type: none"> - Alarm log / Device error log / Network error log on the function panel - Alarm log / Device error log / Network error log / System log / Operation log in [Setting] tab-> [Maintenance]-> [Application log] <p>(Occurrence frequency: High)</p>	<p>When either of the followings is performed:</p> <ul style="list-style-type: none"> - Upgrade WV-ASM300 from V3.10 to V4.00 - Load the setup data of WV-ASM300 V3.10 into WV-ASM300 V4.00 	Fixed.

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
4.10 (3.2.6.0) Mar., '21	C				x	-	-	Supports new cameras: WV-S4151, WV-S4551L, WV-X4172, WV-X4173, WV-X4573L, WV-S8531N, and WV-X8571N
					x	-	-	Supports new firmware version 4.30 of WJ-NX400K, NX300, and NX200
					x	-	-	Added the [Secure communication setup] tab to the [Communication] page. WV-ASM300 performs security certificate check when "ON" is selected for the following on/off settings on this tab: 1. "Certificate check" - Checks if the security certificate is issued by a trusted certificate authority 2. "Certificate expiration check" - Checks if the security certificate is valid 3. "Certificate address mismatch check" - Checks if the address of the security certificate is matched with the address of the device registered 4. "Exclude mismatch check in IP address format" - Excludes mismatch check of the devices registered using IP address *Available only when "ON" is selected for "Certificate address mismatch check"
					x	-	-	Added the "Single PTZ display format for fisheye image (5M/9M fisheye camera)" setting to [Drawing and audio setup] in [System], which enables image dewarping in the same correction method regardless of resolution: 1. "Standard display" - Conventional correction method. WV-ASM300 displays a dewarped image in "Wide area display" or "Center area display" depending on the resolution. 2. "Wide area display" - Correction method that displays a wide area of an image. *Note that periphery of the image can be distorted. 3. "Center area display" - Correction method that displays the center area of an image to reduce image distortion. Applicable models: WV-S4150, WV-S4550L, WV-SFV481, WV-SFN480, WV-X4170, WV-X4171, WV-X4571L, WV-S4151, WV-S4551L, WV-X4172, WV-X4173, and WV-X4573L
					x	-	-	Improved the operability of thumbnail search as below: By selecting a thumbnail, WV-ASM300 automatically displays the date and time of the selected thumbnail under "Start" of the function panel.
					x	-	-	Improved the search function on the operation window to be able to search devices under the "Download panel".
			x	-	-	Improved the recorder / folder search result as below: WV-ASM300 displays the cameras registered in the recorder / folder on the following windows: - Function panel on the operation window (Search function) - Setup page (Filter function)		

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence
	A	B	C	U			
4.10 (3.2.6.0) Mar., '21	Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)						Contents
	C			x	-	-	Added the "Release of alarm state" on/off setting to the [Alarm] page in [Event]. When it is set to "ON", an alarm can be stopped through the following operations. Operation from WV-ASM300: 1. By clicking the [Live] button / the [Play] button on the pop-up window of alarm notification message: - Output of buzzer sound stops - The camera icon blinking or turned red on the map window returns to normal status 2. By clicking the [Close] button on the pop-up window of alarm notification message: - Output of buzzer sound stops Operation from WV-CU950: By pressing [Alarm/Alarm suspend button (ALARM/ALM SUSPEND)] / [Alarm Acknowledge button (ACK)]: - Output of buzzer sound stops - The camera icon blinking or turned red on the map window returns to normal status Operation from WV-CU980: By pressing the [ALM LIVE] button / the [ALM PLAY] button: - Output of buzzer sound stops - The camera icon blinking or turned red on the map window returns to normal status
			x		WV-ASM300 fails in the following operations on [Initial setup] and [Advanced setup] windows : - Acquiring information of a recorder - Transmitting the setting values to a recorder (Occurrence frequency: High)	When satisfying both of below conditions: - The recorder is version 3.10 or later of NX400, NX300, or NX200 - In the recorder setting, [Do not use stream 2 of camera with each function of this recorder.] in [Camera]-> [Advanced setup] is checked	Fixed.
			x	WV-ASM300 may not display the following information correctly when using the data encryption function between WV-ASF950 and WV-ASM300: - Information of the registered person on the face matching alarm notification window (pop-up window) - "Name" and "Remarks" of the registered person on the [Alarm] tab in the face search monitor (Occurrence frequency: High)	When satisfying all of below conditions: - WV-ASM300 is version 3.10, 4.00, or 4.01 - The encryption key is registered in the WV-ASF950 connected to WV-ASM300 - The operation mode of the facial recognition server is "registered face detection" - WV-ASM300 continuously receives face matching alarm	Fixed.	

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
4.20 (3.3.0.0) June, '21	C				x	-	-	Supports new cameras: WV-S1136, WV-S2136, WV-S2136L, and WV-S2236L
					x	-	-	Supports new firmware version 4.40 of WJ-NX400K, NX300, NX200, and NX100
					x	-	-	Supports detection frame display for AI Occupancy Detection (WV-XAE207W)
					x	-	-	Added "In-screen character 2" setting to the [Camera detail setup] window in [Device setup]-> [Advanced setup]-> [Step2 Camera registration], for the cameras that support two-line display in [Camera title on screen].
					x	-	-	Added "Designate a web browser app" setting to the [GUI display setup] tab on the [System] setting window. WV-ASM300 opens either selected browser or Internet Explorer depending on the camera model, when "Browser start" is clicked on the device tree window. - Opens the browser selected in "Designate a web browser app" in case of a camera that does not support Internet Explorer *Selectable browsers: Default browser on PC, Microsoft Edge (Chromium version), Google Chrome, or Firefox - Opens Internet Explorer in case of a camera that supports Internet Explorer
					x	-	-	Changed the function name from "Display AI-VMD information" to "Detection frame information display" on the following windows. - [Operation window display setup] screen in [Menu] - The pop-up menu on the live window
					x	-	-	Changed the tab name from "AI-VMD" to "Alarm name setting" on the [AI camera] window.
					x	-	-	Added the following warning message when [Halftone (Anti-aliasing)] is set to "ON" in the [Drawing and audio setup] tab. "When "On" is selected, CPU load will become high. Delays may be observed in live video or playback video or it may have difficulty in displaying live video or playback video if operation is performed under an environment with a high resolution, a high frame rate and many number of image display screens or depending on the PC environment."
			x	WV-ASM300 incorrectly displays the following message while playing back the recorded images on a multi-screen. "The selected image compression method is different from the camera's. Change the setting." (Occurrence frequency: High)	When satisfying all of the following conditions: 1. WV-ASM300 is version 3.00 or later 2. Recording the images from a camera whose [Stream encoding format] is set to "H.265", on a NX series recorder 3. Displaying camera images on a multi-screen including the camera in above "2" 4. Performing event recording or schedule recording at constant time interval on the recorder 5. The multi-screen includes a camera with no recording data at or after the designated date & time	Fixed.		

Added in Aug., 2021

VER (ActiveX VER) Release Date	Priority Rank Level				Contents			
	A	B	C	U				
4.20 (3.3.0.0) June, '21	C			x	<p>WV-ASM300 fails to acquire the error log from a NX series recorder. (Occurrence frequency: High)</p>	<p>When satisfying all of the following conditions: 1. Version 1.00 or later of WV-NX300 Version 2.00 or later of WV-NX400 2. "Mirroring mode" is selected for [HDD operational mode] in the recorder 3. The recorder has any one of the following logs: - MIRROR RECOVERY START - MIRROR RECOVERY COMPLETE - MIRROR RECOVERY FAILURE - RAID 1 1 DOWN</p>	Fixed.	
					x	-	-	Supports new cameras: WV-S1536L, WV-S1536LN, WV-S2536L, WV-S2536LN, WV-U2132LA, WV-U2142LA, WV-U2532LA, WV-U2542LA, WV-U1130A, WV-U1132A, WV-U1142A, WV-U1532LA, WV-U1542LA, WV-U2130LA, WV-U2140LA, WV-U2530LA, WV-U2540LA
4.30 (3.3.1.0) Sept., '21	C			x	<p>WV-ASM300 may display an unnecessary error pop-up message "The selected image compression method is different from the camera's. Change the setting." (Occurrence frequency: Low)</p>	<p>When the setting is changed under both of the following conditions: - WV-ASM300 is performing sequence display - The sequence display includes both H.264 and H.265 camera images</p>	Fixed.	
				x	<p>WV-ASM300 does not play back the images smoothly even when "Smooth display (buffering)" is set to "ON" on the [Drawing and audio setup] page. (Occurrence frequency: High)</p>	<p>Under both of the following conditions: - Play back the images of SD memory backup data from WJ-NX400K, NX300, NX200, or NX100 - Use the "Quick playback" panel for the playback</p>	Fixed.	
					x	-	-	Improved to display the following warning message when the [Save] button of "Save as a backup" is clicked on [Maintenance]-> [Save/Load] screen, after the installation of additional application for WV-ASM300: "The setting data of the registered additional application will not be saved. With respect to the setting data of the additional application, save it using the additional application"
					x	-	-	Enabled Message ID setting for Extension software alarm No.1 to No.4 on [AI camera]-> [Alarm name setting] page. Selectable number: from 32 to 175

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Contents	
	A	B	C	U		Occurrence condition	Correspondence
4.31 (3.3.1.0) Sept., '21					WV-ASM300 may restart. (Occurrence frequency: Rare)	<p>When the operation in [Case1] or [Case2] is performed:</p> <p>[Case1] Hide and reopen a function panel (Folder tree / Group / Sequence / Download) of [Operation window] or [Live window] under both of the following conditions: - Folders in multiple levels are open on the function panel - Scroll bar is displayed and scrolled down</p> <p>[Case2] Scroll up and down repeatedly on a function panel (Folder tree / Group / Sequence / Download) of [Operation window] or [Live window], or on the "Search by" section of the [Search] window, under both of the following conditions: - Folders in multiple levels are open - Scroll bar is displayed</p>	Fixed.
4.40 (3.3.3.0) Nov., '21	C			x	-	-	Supports new cameras: WV-S1536LTN, WV-S2536LTN, WV-S4156, WV-S4176, WV-S4556L, WV-S4576L
				x	-	-	Supports new firmware version 4.60 of WJ-NX400K, NX300, NX200, and NX100.
				x	-	-	Supports Microsoft Edge IE mode to access cameras and recorders. WV-ASM300 opens the following browser depending on the model. 1. Devices that support Microsoft Edge, Google Chrome, and Firefox: - The browser selected in "Designate a web browser app" on the [GUI display setup] tab Note: Microsoft Edge IE mode opens depending on the model in use 2. Devices that do not support Microsoft Edge, Google Chrome, and Firefox: - Microsoft Edge in IE mode
			x	-	-	Supports displaying detection frame for AI Face Detection and WV-SAEASF Type5 installed on a network camera. Note: When a camera is connected via an NX series recorder, the recorder needs to be version 4.60 or later	

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
4.40 (3.3.3.0) Nov., '21	C				x	-	-	<p>Improved to monitor the CPU usage and physical memory usage of PC on a regular basis. When the usage exceeds the upper limit continuously for a specified number of times, WV-ASM300 displays the following warning messages. Note: Upper limits can be set in "Warning message window display condition setting" in [System]-> [Performance monitoring setting].</p> <p>Warning message for CPU usage: The CPU usage of the PC exceeded xx%. It is necessary to take measures such as closing unnecessary applications or restarting the PC. If a warning is displayed even after taking the above measures, reduce the image capture size of the camera or the frame rate, reduce the number of image display screens, or change the setting of "Smooth display (Buffering)", "High-speed playback smooth mode" and "Halftone (Anti-aliasing)" to "OFF" from "ON".</p> <p>Warning message for physical memory usage: The physical memory usage rate of the PC exceeded xx% due to the running processes on Windows or applications other than this software. Please restart the PC.</p>
					x	-	-	<p>Improved to display the following warning message when WV-ASM300 has automatically lowered the frame rate while displaying images on a multi-screen at high resolution.</p> <p>Warning message: Drawing is being processed with a reduced frame rate since images are being displayed with a high resolution in a multiple screen. This can be improved by adjusting the settings of the camera or this software.</p>
				x		The CPU usage reaches 100% due to the operation of WV-ASM300 and WV-ASM300 may show slow response. (Occurrence frequency: High)	Pause the multi-screen playback on the operation window	Fixed.
				x		The image selection frames of all cameras blink on a multi-screen for a few seconds. (Occurrence frequency: High)	<p>When satisfying both of the following conditions:</p> <ul style="list-style-type: none"> - 360-degree fisheye camera is included in the multi-screen - Switch the images or screen layout on the multi-screen by one of the following operations: <ol style="list-style-type: none"> 1. Change the camera layout using the page layout icon on the tool bar 2. Select a group in [Group] on the function panel 3. Switch between live image and playback image 	Fixed.

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
4.40 (3.3.3.0) Nov., '21	C			x		WV-ASM300 may playback the latest recorded images of stream 1 instead of stream 2 on a multi-screen. (Occurrence frequency: High)	When satisfying all of the following conditions: - NX series recorder is used for playback - Stream 1 and 2 are used for recording - "Stream (NX series) in multi-display" is set to "Stream 2" on the [Drawing and audio setup] tab - The first playback of the images is performed by clicking the "Go to last" button on the [Quick playback] panel	Fixed.
				x		WV-ASM300 may switch the playback stream from stream 1 to stream 2 after the recovery from a communication error with a recorder. (Occurrence frequency: Low)	When satisfying all of the following conditions: - NX series recorder is used for playback - Stream 1 and 2 are used for recording - "Stream (NX series) in multi-display" is set to "Stream 2" on the [Drawing and audio setup] tab - During a playback on a multi-screen	Fixed.
5.00 (3.3.4.0) Apr., '22	C				x	-	-	Changed company name from "Panasonic i-PRO Sensing Solutions Co., Ltd." to "i-PRO Co., Ltd." Notes after upgrading to version 5.00 or later: - The folder name changes from "Panasonic" to "i-PRO" on the Start menu of the PC - The default folder path at installation changes to "C:\Program Files\i-PRO\ASM300" or "C:\ProgramFiles (x86)\i-PRO\ASM300"
					x	-	-	Supports new cameras: WV-S8543, WV-S8543G, WV-S8544, WV-S8544G, WV-S8543L, WV-S8543LG, WV-S8544L, WV-S8544LG, WV-S8563L, WV-S8563LG, WV-S8564L, WV-S8564LG, WV-S8573L, WV-S8573LG, WV-S8574L, WV-S8574LG WV-S15500-V3LN, WV-S15700-V2LN, WV-S25500-V3LN, WV-S25700-V2LN, WV-S22500-V3L, WV-S22700-V2L Added in June, 2022 WV-S15500-V3L, WV-S15500-V3LN1, WV-S15500-V3LK, WV-S15500-F3L, WV-S15500-F6L, WV-S15600-V2L, WV-S15600-V2LN, WV-S15700-V2L, WV-S15700-V2LK, WV-S22500-V3LG, WV-S22500-V3L1, WV-S22500-F3L, WV-S22500-F6L, WV-S22600-V2L, WV-S22600-V2LG, WV-S22700-V2LG, WV-S22700-V2L1, WV-S25500-V3L, WV-S25500-V3LG, WV-S25500-V3LN1, WV-S25500-F3L, WV-S25500-F6L, WV-S25600-V2L, WV-S25600-V2LN, WV-S25600-V2LG, WV-S25700-V2L, WV-S25700-V2LG, WV-S25700-V2LN1, WV-S71300-F3
					x	-	-	Supports new firmware version 5.00 of WJ-NX400K, NX300, NX200 and NX100.
					x	-	-	Improved the operability when the "Return to regular icons" is clicked on the [Device tree] panel as follows: - Enables the image display on the [Group] and [Sequence] panels, if the camera connection is recovered.

VER (ActiveX VER) Release Date	Priority Rank Level				Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)	Contents		
	A	B	C	U		Issue (Phenomenon)	Occurrence condition	Correspondence
5.00 (3.3.4.0) Apr., '22	C			x		Unnecessary image selection frame appears during sequence operation. (Occurrence frequency: High)	When image drawing process restarts unexpectedly during sequence operation.	Fixed.
				x		WV-ASM300 may start up without user authentication. (Occurrence frequency: Low)	Under both of the following conditions: - The PC is restarted without closing WV-ASM300 - [User authentication] is set to "ON" on the [User management]-> [Basic setup] tab.	Fixed.
				x		Live window and map window do not start automatically. (Occurrence frequency: High)	When the following steps are performed while [User authentication] is set to "ON": 1. Start WV-ASM300 and click the [Cancel] button on the login window 2. Start WV-ASM300 again and login to WV-ASM300	Fixed.
				x		Live window and map window may not start automatically. (Occurrence frequency: Low)	When the following steps are performed while Live monitor or Map monitor is opened as a tab: - Restart the PC without closing WV-ASM300 - Start WV-ASM300	Fixed.
					x	-	-	Improved the startup performance of Live monitor and Map monitor after restarting the PC without closing WV-ASM300.
5.01 (3.3.4.0) Apr., '22	C			x		Unable to playback the recorded images of WJ-NV300 or WJ-NV200 on the Operation window. (Occurrence frequency: High)	When satisfying both of the following conditions: - WV-ASM300 is version 5.00 - The compression method of the recorded image is H.264	Fixed.
				x		Unable to playback the n3r file downloaded from WJ-NV300 or WJ-NV200 on the NX Viewer. (Occurrence frequency: High)	When satisfying all of the following conditions: - WV-ASM300 is version 5.00 - The NX Viewer is downloaded from WV-ASM300 - The compression method of the recorded image is H.264	Fixed.

VER (ActiveX VER) Release Date	Priority Rank Level				Issue (Phenomenon)	Occurrence condition	Correspondence	
	A	B	C	U				
5.10 (3.3.6.0) June, '22	B				x	-	-	Supports new cameras: WV-S61301-Z2, WV-S65340-Z4N, WV-S65340-Z4K, WV-S65340-Z2N, WV-S65340-Z2K, WV-S61302-Z4, WV-U65302-Z2, WV-U65302-Z2G, WV-U65301-Z1, WV-U65301-Z1G, WV-U65300-ZY, WV-U65300-ZYG, WV-U61301-Z2, WV-U61301-Z1, WV-U61300-ZY, WV-U61300-ZYG
					x	-	-	Supports new firmware version 5.10 of WJ-NX400K, NX300, NX200 and NX100.
					x	-	-	Added the on/off setting of [The EL-zoom function for fixed cameras (when "Camera control" is not selected in user level setup)] on the [Drawing and audio setup] tab. Selecting "On" enables the users without camera control permission to use EL-zoom function by mouse drag and mouse wheel on the image of fixed camera.
					x	-	-	Improved to display the following warning message when installing the extension software other than "i-PRO Active Guard plug-in for WV-ASM300" on the PC with "i-PRO Active Guard Server" already installed. Displayed message: Extension software other than WV-ASE335W and additional applications may not work properly because WV-ASA100 is installed. Note: - WV-ASA100 : "i-PRO Active Guard Server" for global market - WV-ASE335W : "i-PRO Active Guard Plug-in for ASM300" for global market
					x	-	-	Improved to cancel the installation of WV-ASM300 and display the following warning message for the proper installation procedure, when i-PRO Active Guard server is already installed on the PC. Displayed message: The installation will be aborted. If ASM300 and i-PRO Active Guard are installed on the same PC, ASM300 must be installed first, then i-PRO Active Guard.
				x	The playback image may freeze for a few seconds to 60 seconds on the multi-screen. (Occurrence frequency: Medium)	When the image is recorded with the following camera settings: - The image capture size is larger than FHD (1920×1080) - [Smart coding (GOP control)] is "ON (Advanced)"	Fixed.	

VER (ActiveX VER) Release Date	Priority Rank Level				Contents		
	A	B	C	U			
5.10 (3.3.6.0) June, '22	Priority Rank Level A: Recommend to apply (Major or serious update) B: When issue happened C: Maintenance timing U: Function /Performance improvement (Not Necessary to update)						
			x		Issue (Phenomenon) The live sequence operation stops and may result in still images, black screen or error message. (Occurrence frequency: High)	Occurrence condition When satisfying all of the following conditions: - The sequence operation is continued for about one week - The following pop-up messages appear frequently during the sequence operation: Alarm notification / Event notification / Warning - Manually or automatically* close the above notification messages *Auto-close of warning messages is available in version 4.40 or later when both [Drawing performance limit warning] and [Automatic closing of warning message window] are set to "ON" in the [Performance monitoring setting] tab.	Correspondence Fixed.
	B			x	Issue (Phenomenon) The focus control incorrectly works on the live image of a camera while playing back its images from the recorder. (Occurrence frequency: High)	Occurrence condition When the focus button is clicked on the [Camera operation panel] of WV-ASM300 or on the System Controller WV-CU980 / CU950 during the playback.	Correspondence Fixed.
				x	Issue (Phenomenon) The camera control of [Auto mode] and [Wiper] incorrectly work on the live image of a camera while playing back its images from the recorder. (Occurrence frequency: High)	Occurrence condition When the "Start" or "Stop" button of the following applicable functions is clicked on the [Camera operation panel] of WV-ASM300 or on the System Controller WV-CU980 / CU950 during the playback. Applicable functions: - [Auto mode] Auto track / Auto pan / Preset sequence / Sort / Patrol - [Wiper]	Correspondence Fixed.

Important notice at upgrading software
 Please save setup data as backup before upgrading. Upgrade WV-ASM300. Then import the setup data.
 Otherwise, lose setup data as follow; (1) Basic setup: Language, Date format, Time format (2) Drawing setup: Contrast enhanced display (RGB:0-256), Audio (3) GUI display setup: Full screen display when opening the operation window (4) Performance setup: HD300 (Live)